

# **Linux Standard Base Core Specification for AMD64 3.0**

## **Linux Standard Base Core Specification for AMD64 3.0**

Copyright © 2004, 2005 Free Standards Group

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Portions of the text are copyrighted by the following parties:

- The Regents of the University of California
- Free Software Foundation
- Ian F. Darwin
- Paul Vixie
- BSDI (now Wind River)
- Andrew G Morgan
- Jean-loup Gailly and Mark Adler
- Massachusetts Institute of Technology

These excerpts are being used in accordance with their respective licenses.

Linux is a trademark of Linus Torvalds.

UNIX a registered trademark of the Open Group in the United States and other countries.

LSB is a trademark of the Free Standards Group in the USA and other countries.

AMD is a trademark of Advanced Micro Devices, Inc.

Intel and Itanium are registered trademarks and Intel386 is a trademarks of Intel Corporation.

PowerPC and PowerPC Architecture are trademarks of the IBM Corporation.

OpenGL is a registered trademark of Silicon Graphics, Inc.

# Contents

<b>Foreword</b> .....	<b>vi</b>
<b>Introduction</b> .....	<b>vii</b>
<b>I Introductory Elements</b> .....	<b>8</b>
1 Scope.....	8
1.1 General.....	8
1.2 Module Specific Scope.....	8
2 Normative References.....	9
3 Requirements .....	13
3.1 Relevant Libraries .....	13
3.2 LSB Implementation Conformance .....	13
3.3 LSB Application Conformance.....	14
4 Definitions .....	15
5 Terminology .....	16
6 Documentation Conventions .....	18
<b>II Executable and Linking Format (ELF)</b> .....	<b>19</b>
7 Introduction.....	19
8 Low Level System Information.....	20
8.1 Machine Interface.....	20
8.2 Function Calling Sequence.....	21
8.3 Operating System Interface .....	22
8.4 Process Initialization.....	22
8.5 Coding Examples .....	22
8.6 C Stack Frame .....	23
8.7 Debug Information .....	23
9 Object Format .....	24
9.1 Introduction .....	24
9.2 ELF Header .....	24
9.3 Sections.....	24
9.4 Symbol Table .....	25
9.5 Relocation.....	25
10 Program Loading and Dynamic Linking .....	26
10.1 Introduction .....	26
10.2 Program Header.....	26
10.3 Program Loading .....	26
10.4 Dynamic Linking.....	26
<b>III Base Libraries</b> .....	<b>28</b>
11 Libraries .....	28
11.1 Program Interpreter/Dynamic Linker .....	28
11.2 Interfaces for libc .....	28
11.3 Data Definitions for libc .....	44
11.4 Interfaces for libm .....	52
11.5 Data Definitions for libm.....	57
11.6 Interfaces for libpthread.....	58
11.7 Interfaces for libgcc_s .....	60
11.8 Interface Definitions for libgcc_s.....	61
11.9 Interfaces for libdl .....	61
11.10 Interfaces for libcrypt.....	62

<b>IV Utility Libraries.....</b>	<b>63</b>
12 Libraries .....	63
12.1 Interfaces for libz.....	63
12.2 Interfaces for libncurses.....	63
12.3 Interfaces for libutil.....	63
<b>V Package Format and Installation .....</b>	<b>65</b>
13 Software Installation .....	65
13.1 Package Dependencies .....	65
13.2 Package Architecture Considerations .....	65
<b>A Alphabetical Listing of Interfaces.....</b>	<b>66</b>
A.1 libgcc_s.....	66
A.2 libm.....	66
<b>B GNU Free Documentation License .....</b>	<b>67</b>
B.1 PREAMBLE .....	67
B.2 APPLICABILITY AND DEFINITIONS .....	67
B.3 VERBATIM COPYING.....	68
B.4 COPYING IN QUANTITY .....	68
B.5 MODIFICATIONS .....	69
B.6 COMBINING DOCUMENTS.....	70
B.7 COLLECTIONS OF DOCUMENTS.....	71
B.8 AGGREGATION WITH INDEPENDENT WORKS.....	71
B.9 TRANSLATION .....	71
B.10 TERMINATION .....	71
B.11 FUTURE REVISIONS OF THIS LICENSE .....	71
B.12 How to use this License for your documents.....	72

## List of Tables

2-1 Normative References .....	9
3-1 Standard Library Names .....	13
9-1 ELF Special Sections .....	24
9-2 Additional Special Sections .....	25
11-1 libc Definition .....	28
11-2 libc - RPC Function Interfaces .....	28
11-3 libc - System Calls Function Interfaces .....	29
11-4 libc - Standard I/O Function Interfaces .....	31
11-5 libc - Standard I/O Data Interfaces .....	32
11-6 libc - Signal Handling Function Interfaces .....	33
11-7 libc - Signal Handling Data Interfaces .....	33
11-8 libc - Localization Functions Function Interfaces .....	34
11-9 libc - Localization Functions Data Interfaces .....	34
11-10 libc - Socket Interface Function Interfaces .....	34
11-11 libc - Wide Characters Function Interfaces .....	35
11-12 libc - String Functions Function Interfaces .....	36
11-13 libc - IPC Functions Function Interfaces .....	38
11-14 libc - Regular Expressions Function Interfaces .....	38
11-15 libc - Character Type Functions Function Interfaces .....	38
11-16 libc - Time Manipulation Function Interfaces .....	39
11-17 libc - Time Manipulation Data Interfaces .....	39
11-18 libc - Terminal Interface Functions Function Interfaces .....	40
11-19 libc - System Database Interface Function Interfaces .....	40
11-20 libc - Language Support Function Interfaces .....	41
11-21 libc - Large File Support Function Interfaces .....	41
11-22 libc - Standard Library Function Interfaces .....	42
11-23 libc - Standard Library Data Interfaces .....	44
11-24 libm Definition .....	52
11-25 libm - Math Function Interfaces .....	53
11-26 libm - Math Data Interfaces .....	56
11-27 libpthread Definition .....	58
11-28 libpthread - Realtime Threads Function Interfaces .....	58
11-29 libpthread - Posix Threads Function Interfaces .....	59
11-30 libpthread - Thread aware versions of libc interfaces Function Interfaces .....	60
11-31 libgcc_s Definition .....	60
11-32 libgcc_s - Unwind Library Function Interfaces .....	61
11-33 libdl Definition .....	61
11-34 libdl - Dynamic Loader Function Interfaces .....	62
11-35 libcrypt Definition .....	62
11-36 libcrypt - Encryption Function Interfaces .....	62
12-1 libz Definition .....	63
12-2 libncurses Definition .....	63
12-3 libutil Definition .....	63
12-4 libutil - Utility Functions Function Interfaces .....	64
A-1 libgcc_s Function Interfaces .....	66
A-2 libm Function Interfaces .....	66

## Foreword

This is version 3.0 of the Linux Standard Base Core Specification for AMD64. This specification is part of a family of specifications under the general title "Linux Standard Base". Developers of applications or implementations interested in using the LSB trademark should see the Free Standards Group Certification Policy for details.

## Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. Since a binary specification shall include information specific to the computer processor architecture for which it is intended, it is not possible for a single document to specify the interface for all possible LSB-conforming implementations. Therefore, the LSB is a family of specifications, rather than a single one.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in the detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form  $x.y$  or  $x.y.z$ . This version number carries the following meaning:

- The first number ( $x$ ) is the major version number. All versions with the same major version number should share binary compatibility. Any addition or deletion of a new library results in a new version number. Interfaces marked as `deprecated` may be removed from the specification at a major version change.
- The second number ( $y$ ) is the minor version number. Individual interfaces may be added if all certified implementations already had that (previously undocumented) interface. Interfaces may be marked as `deprecated` at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
- The third number ( $z$ ), if present, is the editorial level. Only editorial changes should be included in such versions.

# 1 Scope

## 1.1 General

The Linux Standard Base (LSB) defines a system interface for compiled applications and a minimal environment for support of installation scripts. Its purpose is to enable a uniform industry standard environment for high-volume applications conforming to the LSB.

These specifications are composed of two basic parts: A common specification ("LSB-generic") describing those parts of the interface that remain constant across all implementations of the LSB, and an architecture-specific specification ("LSB-arch") describing the parts of the interface that vary by processor architecture. Together, the LSB-generic and the architecture-specific supplement for a single hardware architecture provide a complete interface specification for compiled application programs on systems that share a common hardware architecture.

The LSB-generic document shall be used in conjunction with an architecture-specific supplement. Whenever a section of the LSB-generic specification shall be supplemented by architecture-specific information, the LSB-generic document includes a reference to the architecture supplement. Architecture supplements may also contain additional information that is not referenced in the LSB-generic document.

The LSB contains both a set of Application Program Interfaces (APIs) and Application Binary Interfaces (ABIs). APIs may appear in the source code of portable applications, while the compiled binary of that application may use the larger set of ABIs. A conforming implementation shall provide all of the ABIs listed here. The compilation system may replace (e.g. by macro definition) certain APIs with calls to one or more of the underlying binary interfaces, and may insert calls to binary interfaces as needed.

The LSB is primarily a binary interface definition. Not all of the source level APIs available to applications may be contained in this specification.

## 1.2 Module Specific Scope

This is the AMD64 architecture specific Core module of the Linux Standards Base (LSB). This module supplements the generic LSB Core module with those interfaces that differ between architectures.

Interfaces described in this module are mandatory except where explicitly listed otherwise. Core interfaces may be supplemented by other modules; all modules are built upon the core.



## 2 Normative References

The specifications listed below are referenced in whole or in part by the Linux Standard Base. In this specification, where only a particular section of one of these references is identified, then the normative reference is to that section alone, and the rest of the referenced document is informative.

**Table 2-1 Normative References**

<b>Name</b>	<b>Title</b>	<b>URL</b>
AMD64 Architecture Programmer's Manual, Volume 1	AMD64 Architecture Programmer's Manual, Volume 1: Application Programming 24592 3.08	<a href="http://www.amd.com/us-&lt;br/&gt;en/Processors/Develop&lt;br/&gt;WithAMD/">http://www.amd.com/ us- en/Processors/Develop WithAMD/</a>
AMD64 Architecture Programmer's Manual, Volume 2	AMD64 Architecture Programmer's Manual, Volume 2: System Programming 24593 3.08	<a href="http://www.amd.com/us-&lt;br/&gt;en/Processors/Develop&lt;br/&gt;WithAMD/">http://www.amd.com/ us- en/Processors/Develop WithAMD/</a>
AMD64 Architecture Programmer's Manual, Volume 3	AMD64 Architecture Programmer's Manual, Volume 3: General Purpose and System Instructions 24594 3.03	<a href="http://www.amd.com/us-&lt;br/&gt;en/Processors/Develop&lt;br/&gt;WithAMD/">http://www.amd.com/ us- en/Processors/Develop WithAMD/</a>
AMD64 Architecture Programmer's Manual, Volume 4	AMD64 Architecture Programmer's Manual, Volume 4: 128-bit Media Instructions 26568 3.04	<a href="http://www.amd.com/us-&lt;br/&gt;en/Processors/Develop&lt;br/&gt;WithAMD/">http://www.amd.com/ us- en/Processors/Develop WithAMD/</a>
AMD64 Architecture Programmer's Manual, Volume 5	AMD64 Architecture Programmer's Manual, Volume 5: 64-bit Media and x87 Floating-Point Instructions 26569 3.03	<a href="http://www.amd.com/us-&lt;br/&gt;en/Processors/Develop&lt;br/&gt;WithAMD/">http://www.amd.com/ us- en/Processors/Develop WithAMD/</a>
DWARF Debugging Information Format, Revision 2.0.0	DWARF Debugging Information Format, Revision 2.0.0 (July 27, 1993)	<a href="http://refspecs.freestand&lt;br/&gt;ards.org/dwarf/dwarf-&lt;br/&gt;2.0.0.pdf">http://refspecs.freestand ards.org/dwarf/dwarf- 2.0.0.pdf</a>
DWARF Debugging Information Format, Revision 3.0.0 (Draft)	DWARF Debugging Information Format, Revision 3.0.0 (Draft)	<a href="http://refspecs.freestand&lt;br/&gt;ards.org/dwarf/">http://refspecs.freestand ards.org/dwarf/</a>
Filesystem Hierarchy Standard	Filesystem Hierarchy Standard (FHS) 2.3	<a href="http://www.pathname.c&lt;br/&gt;om/fhs/">http://www.pathname.c om/fhs/</a>
IEC 559/IEEE 754 Floating Point	IEC 559:1989 Binary floating-point arithmetic for microprocessor systems	<a href="http://www.ieee.org/">http://www.ieee.org/</a>
ISO C (1999)	ISO/IEC 9899: 1999, Programming Languages	

2 Normative References

Name	Title	URL
	--C	
ISO POSIX (2003)	<p>ISO/IEC 9945-1:2003 Information technology - - Portable Operating System Interface (POSIX) -- Part 1: Base Definitions</p> <p>ISO/IEC 9945-2:2003 Information technology - - Portable Operating System Interface (POSIX) -- Part 2: System Interfaces</p> <p>ISO/IEC 9945-3:2003 Information technology - - Portable Operating System Interface (POSIX) -- Part 3: Shell and Utilities</p> <p>ISO/IEC 9945-4:2003 Information technology - - Portable Operating System Interface (POSIX) -- Part 4: Rationale Including Technical Cor. 1: 2004</p>	<p><a href="http://www.unix.org/version3/">http://www.unix.org/ version3/</a></p>
ISO/IEC TR14652	<p>ISO/IEC Technical Report 14652:2002 Specification method for cultural conventions</p>	
ITU-T V.42	<p>International Telecommunication Union Recommendation V.42 (2002): Error- correcting procedures for DCEs using asynchronous-to- synchronous conversion ITUV</p>	<p><a href="http://www.itu.int/rec/recommendation.asp?type=folders&amp;lang=e&amp;parent=T-REC-V.42">http://www.itu.int/rec/ recommendation.asp?typ e=folders&amp;lang=e&amp;paren t=T-REC-V.42</a></p>
Large File Support	Large File Support	<p><a href="http://www.UNIX-systems.org/version2/whatsnew/lfs20mar.html">http://www.UNIX- systems.org/version2/w hatsnew/lfs20mar.html</a></p>
Li18nux Globalization Specification	<p>LI18NUX 2000 Globalization Specification, Version 1.0 with Amendment 4</p>	<p><a href="http://www.li18nux.org/docs/html/LI18NUX-2000-amd4.htm">http://www.li18nux.org /docs/html/LI18NUX- 2000-amd4.htm</a></p>

<b>Name</b>	<b>Title</b>	<b>URL</b>
Linux Allocated Device Registry	LINUX ALLOCATED DEVICES	<a href="http://www.lanana.org/docs/device-list/devices.txt">http://www.lanana.org/docs/device-list/devices.txt</a>
PAM	Open Software Foundation, Request For Comments: 86.0 , October 1995, V. Samar & R.Schemers (SunSoft)	<a href="http://www.opengroup.org/tech/rfc/mirror-rfc/rfc86.0.txt">http://www.opengroup.org/tech/rfc/mirror-rfc/rfc86.0.txt</a>
RFC 1321: The MD5 Message-Digest Algorithm	IETF RFC 1321: The MD5 Message-Digest Algorithm	<a href="http://www.ietf.org/rfc/rfc1321.txt">http://www.ietf.org/rfc/rfc1321.txt</a>
RFC 1833: Binding Protocols for ONC RPC Version 2	IETF RFC 1833: Binding Protocols for ONC RPC Version 2	<a href="http://www.ietf.org/rfc/rfc1833.txt">http://www.ietf.org/rfc/rfc1833.txt</a>
RFC 1950: ZLIB Compressed Data Format Specification	IETF RFC 1950: ZLIB Compressed Data Format Specification	<a href="http://www.ietf.org/rfc/rfc1950.txt">http://www.ietf.org/rfc/rfc1950.txt</a>
RFC 1951: DEFLATE Compressed Data Format Specification	IETF RFC 1951: DEFLATE Compressed Data Format Specification version 1.3	<a href="http://www.ietf.org/rfc/rfc1951.txt">http://www.ietf.org/rfc/rfc1951.txt</a>
RFC 1952: GZIP File Format Specification	IETF RFC 1952: GZIP file format specification version 4.3	<a href="http://www.ietf.org/rfc/rfc1952.txt">http://www.ietf.org/rfc/rfc1952.txt</a>
RFC 2440: OpenPGP Message Format	IETF RFC 2440: OpenPGP Message Format	<a href="http://www.ietf.org/rfc/rfc2440.txt">http://www.ietf.org/rfc/rfc2440.txt</a>
RFC 2821: Simple Mail Transfer Protocol	IETF RFC 2821: Simple Mail Transfer Protocol	<a href="http://www.ietf.org/rfc/rfc2821.txt">http://www.ietf.org/rfc/rfc2821.txt</a>
RFC 2822: Internet Message Format	IETF RFC 2822: Internet Message Format	<a href="http://www.ietf.org/rfc/rfc2822.txt">http://www.ietf.org/rfc/rfc2822.txt</a>
RFC 791: Internet Protocol	IETF RFC 791: Internet Protocol Specification	<a href="http://www.ietf.org/rfc/rfc791.txt">http://www.ietf.org/rfc/rfc791.txt</a>
SUSv2	CAE Specification, January 1997, System Interfaces and Headers (XSH), Issue 5 (ISBN: 1-85912-181-0, C606)	<a href="http://www.opengroup.org/publications/catalog/un.htm">http://www.opengroup.org/publications/catalog/un.htm</a>
SUSv2 Commands and Utilities	The Single UNIX® Specification(SUS) Version 2, Commands and Utilities (XCU), Issue 5 (ISBN: 1-85912-191-8, C604)	<a href="http://www.opengroup.org/publications/catalog/un.htm">http://www.opengroup.org/publications/catalog/un.htm</a>

## 2 Normative References

Name	Title	URL
SVID Issue 3	American Telephone and Telegraph Company, System V Interface Definition, Issue 3 ; Morristown, NJ, UNIX Press, 1989.(ISBN 0201566524)	
SVID Issue 4	System V Interface Definition,Fourth Edition	
System V ABI	System V Application Binary Interface, Edition 4.1	<a href="http://www.caldera.com/developers/devspecs/gabi41.pdf">http://www.caldera.com/developers/devspecs/gabi41.pdf</a>
System V ABI Update	System V Application Binary Interface - DRAFT - 17 December 2003	<a href="http://www.caldera.com/developers/gabi/2003-12-17/contents.html">http://www.caldera.com/developers/gabi/2003-12-17/contents.html</a>
System V Application Binary Interface AMD64 Architecture Processor Supplement	System V Application Binary Interface AMD64 Architecture Processor Supplement, Draft Version 0.95	<a href="http://www.x86-64.org/documentation/abi-0.95.pdf">http://www.x86-64.org/documentation/abi-0.95.pdf</a>
this specification	Linux Standard Base	<a href="http://www.linuxbase.org/spec/">http://www.linuxbase.org/spec/</a>
X/Open Curses	CAE Specification, May 1996, X/Open Curses, Issue 4, Version 2 (ISBN: 1-85912-171-3, C610), plus Corrigendum U018	<a href="http://www.opengroup.org/publications/catalog/un.htm">http://www.opengroup.org/publications/catalog/un.htm</a>

## 3 Requirements

### 3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on x86-64 Linux Standard Base systems, with the specified runtime names. These names override or supplement the names specified in the generic LSB specification. The specified program interpreter, referred to as `proginterp` in this table, shall be used to load the shared libraries specified by `DT_NEEDED` entries at run time.

**Table 3-1 Standard Library Names**

<b>Library</b>	<b>Runtime Name</b>
libm	libm.so.6
libdl	libdl.so.2
libcrypt	libcrypt.so.1
libz	libz.so.1
libncurses	libncurses.so.5
libutil	libutil.so.1
libc	libc.so.6
libpthread	libpthread.so.0
proginterp	/lib64/ld-lsb-x86-64.so.3
libgcc_s	libgcc_s.so.1

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

### 3.2 LSB Implementation Conformance

A conforming implementation shall satisfy the following requirements:

- The implementation shall implement fully the architecture described in the hardware manual for the target processor architecture.
- The implementation shall be capable of executing compiled applications having the format and using the system interfaces described in this document.
- The implementation shall provide libraries containing the interfaces specified by this document, and shall provide a dynamic linking mechanism that allows these interfaces to be attached to applications at runtime. All the interfaces shall behave as specified in this document.
- The map of virtual memory provided by the implementation shall conform to the requirements of this document.
- The implementation's low-level behavior with respect to function call linkage, system traps, signals, and other such activities shall conform to the formats described in this document.
- The implementation shall provide all of the mandatory interfaces in their entirety.

- The implementation may provide one or more of the optional interfaces. Each optional interface that is provided shall be provided in its entirety. The product documentation shall state which optional interfaces are provided.
- The implementation shall provide all files and utilities specified as part of this document in the format defined here and in other referenced documents. All commands and utilities shall behave as required by this document. The implementation shall also provide all mandatory components of an application's runtime environment that are included or referenced in this document.
- The implementation, when provided with standard data formats and values at a named interface, shall provide the behavior defined for those values and data formats at that interface. However, a conforming implementation may consist of components which are separately packaged and/or sold. For example, a vendor of a conforming implementation might sell the hardware, operating system, and windowing system as separately packaged items.
- The implementation may provide additional interfaces with different names. It may also provide additional behavior corresponding to data values outside the standard ranges, for standard named interfaces.

### 3.3 LSB Application Conformance

A conforming application shall satisfy the following requirements:

- Its executable files are either shell scripts or object files in the format defined for the Object File Format system interface.
- Its object files participate in dynamic linking as defined in the Program Loading and Linking System interface.
- It employs only the instructions, traps, and other low-level facilities defined in the Low-Level System interface as being for use by applications.
- If it requires any optional interface defined in this document in order to be installed or to execute successfully, the requirement for that optional interface is stated in the application's documentation.
- It does not use any interface or data format that is not required to be provided by a conforming implementation, unless:
  - If such an interface or data format is supplied by another application through direct invocation of that application during execution, that application is in turn an LSB conforming application.
  - The use of that interface or data format, as well as its source, is identified in the documentation of the application.
- It shall not use any values for a named interface that are reserved for vendor extensions.

A strictly conforming application does not require or use any interface, facility, or implementation-defined extension that is not defined in this document in order to be installed or to execute successfully.

## 4 Definitions

For the purposes of this document, the following definitions, as specified in the *ISO/IEC Directives, Part 2, 2001, 4th Edition*, apply:

can

be able to; there is a possibility of; it is possible to

cannot

be unable to; there is no possibility of; it is not possible to

may

is permitted; is allowed; is permissible

need not

it is not required that; no...is required

shall

is to; is required to; it is required that; has to; only...is permitted; it is necessary

shall not

is not allowed [permitted] [acceptable] [permissible]; is required to be not; is required that...be not; is not to be

should

it is recommended that; ought to

should not

it is not recommended that; ought not to

## 5 Terminology

For the purposes of this document, the following terms apply:

### archLSB

The architectural part of the LSB Specification which describes the specific parts of the interface that are platform specific. The archLSB is complementary to the gLSB.

### Binary Standard

The total set of interfaces that are available to be used in the compiled binary code of a conforming application.

### gLSB

The common part of the LSB Specification that describes those parts of the interface that remain constant across all hardware implementations of the LSB.

### implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

### Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

### Source Standard

The set of interfaces that are available to be used in the source code of a conforming application.

### undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

### unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.



Other terms and definitions used in this document shall have the same meaning as defined in Chapter 3 of the Base Definitions volume of ISO POSIX (2003).

## 6 Documentation Conventions

Throughout this document, the following typographic conventions are used:

`function()`

the name of a function

**command**

the name of a command or utility

CONSTANT

a constant value

*parameter*

a parameter

variable

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

name

the name of the interface

(symver)

An optional symbol version identifier, if required.

[*refno*]

A reference number indexing the table of referenced specifications that follows this table.

For example,

<code>forkpty(GLIBC_2.0) [1]</code>
-------------------------------------

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the first of the listed references below the table.

## 7 Introduction

Executable and Linking Format (ELF) defines the object format for compiled applications. This specification supplements the information found in System V ABI Update and System V Application Binary Interface AMD64 Architecture Processor Supplement, and is intended to document additions made since the publication of that document.

## 8 Low Level System Information

### 8.1 Machine Interface

#### 8.1.1 Processor Architecture

The AMD64 Architecture is specified by the following documents

- AMD64 Architecture Programmer's Manual, Volume 1
- AMD64 Architecture Programmer's Manual, Volume 2
- AMD64 Architecture Programmer's Manual, Volume 3
- AMD64 Architecture Programmer's Manual, Volume 4
- AMD64 Architecture Programmer's Manual, Volume 5
- System V Application Binary Interface AMD64 Architecture Processor Supplement

Applications conforming to this specification must provide feedback to the user if a feature that is required for correct execution of the application is not present.

Applications conforming to this specification should attempt to execute in a diminished capacity if a required instruction set feature is not present. In particular, applications should not rely on the availability of the 3DNow!™ technology.

**Note:** Although this specification carries the attribution "AMD64", it is intended to apply to the entire x86\_64 set of processors, including those based on Intel® Extended Memory 64 Technology (EM64T). However, this specification defers to the AMD architecture specified above.

An application shall not use CPU instructions that require elevated privileges.

Applications may not make system calls directly. The interfaces in the implementation base libraries must be used instead.

This specification does not provide any performance guarantees of a conforming system. A system conforming to this specification may be implemented in either hardware or software.

#### 8.1.2 Data Representation

##### 8.1.2.1 Introduction

LSB-conforming applications shall use the data representation as defined in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

**Note:** The System V Application Binary Interface AMD64 Architecture Processor Supplement specification is itself layered on top of the System V Application Binary Interface - Intel386™ Architecture Processor Supplement.

##### 8.1.2.2 Byte Ordering

LSB-conforming applications shall use the byte ordering defined in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.1.2.3 Fundamental Types**

LSB-conforming applications shall use only the fundamental types described in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.1.2.4 Aggregates and Unions**

LSB-conforming applications shall use alignment for aggregates and unions as described in Section 3.1.2 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.1.2.5 Bit Fields**

LSB-conforming applications utilizing bit-fields shall follow the requirements of Section 3.1.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## **8.2 Function Calling Sequence**

### **8.2.1 Introduction**

LSB-conforming applications shall use only the following features of the function calling sequence as defined in Section 3.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.2.2 Registers**

LSB-conforming applications shall use only the registers described in Section 3.2.1 (Registers and the Stack Frame) of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.2.3 Floating Point Registers**

LSB-conforming applications shall use only the floating point registers described in Section 3.2.1 (Registers and the Stack Frame) of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.2.4 Stack Frame**

LSB-conforming applications shall use stack frames as described in Section 3.2.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.2.5 Arguments**

LSB-conforming applications shall pass parameters to functions as described in Section 3.2.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.2.6 Return Values**

Values are returned from functions as described in Section 3.3.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## 8.3 Operating System Interface

LSB-conforming applications shall use only the following features of the Operating System Interfaces as defined in Section 3.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### 8.3.1 Exception Interface

Synchronous and floating point or coprocessor exceptions shall behave as described in Section 3.3.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### 8.3.2 Virtual Address Space

LSB-Conforming applications shall use only the virtual address space described in Section 3.3.2 and 3.3.4 of the System V Application Binary Interface AMD64 Architecture Processor Supplement. Virtual memory page sizes shall be subject to the limitations described in Section 3.3.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## 8.4 Process Initialization

LSB-conforming applications shall use only the following features of the Process Initialization as defined in Section 3.4 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### 8.4.1 Special Registers

During process initialization, the special registers shall be initialized as described in Section 3.4.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### 8.4.2 Process Stack (on entry)

The process stack shall be initialized as described in Section 3.4.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### 8.4.3 Auxiliary Vector

The auxiliary vector shall be initialized as described in Section 3.4.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## 8.5 Coding Examples

LSB-conforming applications may use the coding examples given in Section 3.5 of the System V Application Binary Interface AMD64 Architecture Processor Supplement to guide implementation of fundamental operations in the following areas.

### 8.5.1 Code Model Overview/Architecture Constraints

Section 3.5.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement describes a number of code models. LSB-Conforming applications may use any of these models except the Kernel and Large code models.

### **8.5.2 Position-Independent Function Prologue**

LSB-conforming applications may follow the position-independent function prologue example in Section 3.5.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.5.3 Data Objects**

LSB-conforming applications may follow the data objects examples in Section 3.5.4 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.5.4 Function Calls**

LSB-conforming applications may follow the function call examples in Section 3.5.5 of the System V Application Binary Interface AMD64 Architecture Processor Supplement. See Chapter 3 of System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **8.5.5 Branching**

LSB-conforming applications may follow the branching examples in Section 3.5.6 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## **8.6 C Stack Frame**

### **8.6.1 Variable Argument List**

LSB-Conforming applications shall only use variable arguments to functions in the manner described in Section 3.5.7 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## **8.7 Debug Information**

LSB-Conforming applications may include DWARF debugging information. The DWARF Release Number and Register Number Mapping shall be as described in Section 3.6 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## 9 Object Format

### 9.1 Introduction

LSB-conforming implementations shall support the Executable and Linking Format (ELF) object file, as defined by the System V ABI, System V ABI Update, System V Application Binary Interface AMD64 Architecture Processor Supplement and as supplemented by the generic LSB specification and this specification.

### 9.2 ELF Header

#### 9.2.1 Machine Information

LSB-conforming applications shall identify the Machine Information as defined in Section 4.1.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### 9.3 Sections

#### 9.3.1 Introduction

In addition to the requirements for ELF sections described in the generic LSB Core specification, conforming implementations shall support architecture specific sections as described below.

**Note:** The System V Application Binary Interface AMD64 Architecture Processor Supplement specifies some architecture specific section flags and section types that are not required by LSB-conforming systems.

#### 9.3.2 Special Sections

The following architecture-specific sections are defined in the System V Application Binary Interface AMD64 Architecture Processor Supplement.

**Table 9-1 ELF Special Sections**

Name	Type	Attributes
.got	SHT_PROGBITS	SHF_ALLOC+SHF_WRITE
.plt	SHT_PROGBITS	SHF_ALLOC+SHF_EXECINSTR

.got

This section holds the global offset table

.plt

This section holds the procedure linkage table.

**Note:** Since LSB-conforming implementations are not required to support the large code model, it is not necessary for them to provide support for the additional special sections for the large code model described in the System V Application Binary Interface AMD64 Architecture Processor Supplement.



Also, the System V Application Binary Interface AMD64 Architecture Processor Supplement specifies a section `.eh_frame`, with a type of `SHT_AMD64_UNWIND`. This section is described in the generic LSB-Core specification, but with type `SHT_PROGBITS`. This specification does not require support for the `SHT_AMD64_UNWIND` section type.

### 9.3.3 Additional Special Sections

The following additional sections are defined here.

**Table 9-2 Additional Special Sections**

Name	Type	Attributes
<code>.rela.dyn</code>	<code>SHT_RELA</code>	<code>SHF_ALLOC</code>
<code>.rela.plt</code>	<code>SHT_RELA</code>	<code>SHF_ALLOC</code>

`.rela.dyn`

This section holds RELA type relocation information for all sections of a shared library except the PLT

`.rela.plt`

This section holds RELA type relocation information for the PLT section of a shared library or dynamically linked application

## 9.4 Symbol Table

LSB-conforming applications shall use Symbol Tables as defined in Section 4.3 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## 9.5 Relocation

LSB-conforming implementation shall support the required relocation types defined in Section 4.4.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

**Note:** Since LSB-conforming implementations are not required to support the large code model, it is not necessary for them to provide support for the additional relocation types for the large code model described in the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## 10 Program Loading and Dynamic Linking

### 10.1 Introduction

LSB-conforming implementations shall support the object file information and system actions that create running programs as specified in the System V ABI , System V ABI Update , System V Application Binary Interface AMD64 Architecture Processor Supplement and as supplemented by the generic LSB specification and this specification.

### 10.2 Program Header

LSB-conforming implementations are not required to support the additional types and flags for this architecture as defined in Section 5.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

**Note:** The System V Application Binary Interface AMD64 Architecture Processor Supplement specification is itself layered on top of the System V Application Binary Interface - Intel386™ Architecture Processor Supplement. As such, the requirements of that specification are still requirements of this specification.

### 10.3 Program Loading

LSB-conforming implementations shall map file pages to virtual memory pages as described in Section 5.1 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### 10.4 Dynamic Linking

#### 10.4.1 Introduction

LSB-conforming implementations shall provide dynamic linking as specified in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement, except as described in the following sections.

**Note:** Since LSB-conforming implementations are not required to support the large model, support for dynamic linking of large model code is not required.

#### 10.4.2 Dynamic Section

Dynamic section entries give information to the dynamic linker. The following dynamic entry types shall be supported:

DT\_JMPREL

This entry is associated with a table of relocation entries for the procedure linkage table. This entry is mandatory both for executable and shared object files

DT\_PLTGOT

This entry's `d_ptr` member gives the address of the first byte in the procedure linkage table

DT\_RELACOUNT

The number of relative relocations in `.rela.dyn`

### **10.4.3 Global Offset Table**

LSB-conforming implementations shall support a Global Offset Table as described in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **10.4.4 Function Addresses**

Function addresses shall behave as described in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **10.4.5 Procedure Linkage Table**

LSB-conforming implementations shall support a Procedure Linkage Table as described in Section 5.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

### **10.4.6 Initialization and Termination Functions**

LSB-conforming implementations shall support initialization and termination functions as specified in Section 5.2.2 of the System V Application Binary Interface AMD64 Architecture Processor Supplement.

## 11 Libraries

An LSB-conforming implementation shall support some base libraries which provide interfaces for accessing the operating system, processor and other hardware in the system.

Interfaces that are unique to the AMD64 platform are defined here. This section should be used in conjunction with the corresponding section in the Linux Standard Base Specification.

### 11.1 Program Interpreter/Dynamic Linker

The LSB specifies the Program Interpreter to be `/lib64/ld-lsb-x86-64.so.3`.

### 11.2 Interfaces for libc

Table 11-1 defines the library name and shared object name for the libc library

**Table 11-1 libc Definition**

Library:	libc
SONAME:	libc.so.6

The behavior of the interfaces in this library is specified by the following specifications:

Large File Support  
 this specification  
 SUSv2  
 ISO POSIX (2003)  
 SVID Issue 3  
 SVID Issue 4

#### 11.2.1 RPC

##### 11.2.1.1 Interfaces for RPC

An LSB conforming implementation shall provide the architecture specific functions for RPC specified in Table 11-2, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-2 libc - RPC Function Interfaces**

authnone_create(GLIBC_2.5) [1]	svc_getreqset(GLIBC_2.2.5) [2]	svcadp_create(GLIBC_2.2.5) [3]	xdr_int(GLIBC_2.2.5) [2]	xdr_u_long(GLIBC_2.2.5) [2]
clnt_create(GLIBC_2.2.5) [1]	svc_register(GLIBC_2.2.5) [3]	xdr_accepted_reply(GLIBC_2.2.5) [2]	xdr_long(GLIBC_2.2.5) [2]	xdr_u_short(GLIBC_2.2.5) [2]
clnt_pcreateerror(GLIBC_2.2.5) [1]	svc_run(GLIBC_2.2.5) [3]	xdr_array(GLIBC_2.2.5) [2]	xdr_opaque(GLIBC_2.2.5) [2]	xdr_union(GLIBC_2.2.5) [2]
clnt_perrno(G	svc_sendrepl	xdr_bool(GLI	xdr_opaque_a	xdr_vector(G

LIBC_2.2.5) [1]	y(GLIBC_2.2.5) [3]	BC_2.2.5) [2]	uth(GLIBC_2.2.5) [2]	LIBC_2.2.5) [2]
clnt_perror(GLIBC_2.2.5) [1]	svcerr_auth(GLIBC_2.2.5) [2]	xdr_bytes(GLIBC_2.2.5) [2]	xdr_pointer(GLIBC_2.2.5) [2]	xdr_void(GLIBC_2.2.5) [2]
clnt_sprecreateerror(GLIBC_2.2.5) [1]	svcerr_decode(GLIBC_2.2.5) [2]	xdr_callhdr(GLIBC_2.2.5) [2]	xdr_reference(GLIBC_2.2.5) [2]	xdr_wrapstring(GLIBC_2.2.5) [2]
clnt_sperrno(GLIBC_2.2.5) [1]	svcerr_noprocedure(GLIBC_2.2.5) [2]	xdr_callmsg(GLIBC_2.2.5) [2]	xdr_rejected_reply(GLIBC_2.2.5) [2]	xdrmem_create(GLIBC_2.2.5) [2]
clnt_sperror(GLIBC_2.2.5) [1]	svcerr_noprogram(GLIBC_2.2.5) [2]	xdr_char(GLIBC_2.2.5) [2]	xdr_replymsg(GLIBC_2.2.5) [2]	xdrrec_create(GLIBC_2.2.5) [2]
key_decryptsession(GLIBC_2.2.5) [2]	svcerr_providers(GLIBC_2.2.5) [2]	xdr_double(GLIBC_2.2.5) [2]	xdr_short(GLIBC_2.2.5) [2]	xdrrec_eof(GLIBC_2.2.5) [2]
pmap_getport(GLIBC_2.2.5) [3]	svcerr_systemerror(GLIBC_2.2.5) [2]	xdr_enum(GLIBC_2.2.5) [2]	xdr_string(GLIBC_2.2.5) [2]	
pmap_set(GLIBC_2.2.5) [3]	svcerr_weakauth(GLIBC_2.2.5) [2]	xdr_float(GLIBC_2.2.5) [2]	xdr_u_char(GLIBC_2.2.5) [2]	
pmap_unset(GLIBC_2.2.5) [3]	svctcp_create(GLIBC_2.2.5) [3]	xdr_free(GLIBC_2.2.5) [2]	xdr_u_int(GLIBC_2.2.5) [3]	

*Referenced Specification(s)*

[1]. SVID Issue 4

[2]. SVID Issue 3

[3]. this specification

## 11.2.2 System Calls

### 11.2.2.1 Interfaces for System Calls

An LSB conforming implementation shall provide the architecture specific functions for System Calls specified in Table 11-3, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-3 libc - System Calls Function Interfaces**

__fxstat(GLIBC_2.2.5) [1]	fchmod(GLIBC_2.2.5) [2]	getwd(GLIBC_2.2.5) [2]	read(GLIBC_2.2.5) [2]	setrlimit(GLIBC_2.2.5) [2]
__getpgid(GLIBC_2.2.5) [1]	fchown(GLIBC_2.2.5) [2]	initgroups(GLIBC_2.2.5) [1]	readdir(GLIBC_2.2.5) [2]	setrlimit64(GLIBC_2.2.5) [3]

__lxstat(GLIBC_2.2.5) [1]	fcntl(GLIBC_2.2.5) [1]	ioctl(GLIBC_2.2.5) [1]	readdir_r(GLIBC_2.2.5) [2]	setsid(GLIBC_2.2.5) [2]
__xmknod(GLIBC_2.2.5) [1]	fdatasync(GLIBC_2.2.5) [2]	kill(GLIBC_2.2.5) [1]	readlink(GLIBC_2.2.5) [2]	setuid(GLIBC_2.2.5) [2]
__xstat(GLIBC_2.2.5) [1]	flock(GLIBC_2.2.5) [1]	killpg(GLIBC_2.2.5) [2]	readv(GLIBC_2.2.5) [2]	sleep(GLIBC_2.2.5) [2]
access(GLIBC_2.2.5) [2]	fork(GLIBC_2.2.5) [2]	lchown(GLIBC_2.2.5) [2]	rename(GLIBC_2.2.5) [2]	statvfs(GLIBC_2.2.5) [2]
acct(GLIBC_2.2.5) [1]	fstatvfs(GLIBC_2.2.5) [2]	link(GLIBC_2.2.5) [1]	rmdir(GLIBC_2.2.5) [2]	stime(GLIBC_2.2.5) [1]
alarm(GLIBC_2.2.5) [2]	fsync(GLIBC_2.2.5) [2]	lockf(GLIBC_2.2.5) [2]	sbrk(GLIBC_2.2.5) [4]	symlink(GLIBC_2.2.5) [2]
brk(GLIBC_2.2.5) [4]	ftime(GLIBC_2.2.5) [2]	lseek(GLIBC_2.2.5) [2]	sched_get_priority_max(GLIBC_2.2.5) [2]	sync(GLIBC_2.2.5) [2]
chdir(GLIBC_2.2.5) [2]	ftruncate(GLIBC_2.2.5) [2]	mkdir(GLIBC_2.2.5) [2]	sched_get_priority_min(GLIBC_2.2.5) [2]	sysconf(GLIBC_2.2.5) [2]
chmod(GLIBC_2.2.5) [2]	getcontext(GLIBC_2.2.5) [2]	mkfifo(GLIBC_2.2.5) [2]	sched_getparam(GLIBC_2.2.5) [2]	time(GLIBC_2.2.5) [2]
chown(GLIBC_2.2.5) [2]	getegid(GLIBC_2.2.5) [2]	mlock(GLIBC_2.2.5) [2]	sched_getscheduler(GLIBC_2.2.5) [2]	times(GLIBC_2.2.5) [2]
chroot(GLIBC_2.2.5) [4]	geteuid(GLIBC_2.2.5) [2]	mlockall(GLIBC_2.2.5) [2]	sched_rr_get_interval(GLIBC_2.2.5) [2]	truncate(GLIBC_2.2.5) [2]
clock(GLIBC_2.2.5) [2]	getgid(GLIBC_2.2.5) [2]	mmap(GLIBC_2.2.5) [2]	sched_setparam(GLIBC_2.2.5) [2]	ulimit(GLIBC_2.2.5) [2]
close(GLIBC_2.2.5) [2]	getgroups(GLIBC_2.2.5) [2]	mprotect(GLIBC_2.2.5) [2]	sched_setscheduler(GLIBC_2.2.5) [2]	umask(GLIBC_2.2.5) [2]
closedir(GLIBC_2.2.5) [2]	getitimer(GLIBC_2.2.5) [2]	msync(GLIBC_2.2.5) [2]	sched_yield(GLIBC_2.2.5) [2]	uname(GLIBC_2.2.5) [2]
creat(GLIBC_2.2.5) [2]	getloadavg(GLIBC_2.2.5) [1]	munlock(GLIBC_2.2.5) [2]	select(GLIBC_2.2.5) [2]	unlink(GLIBC_2.2.5) [1]
dup(GLIBC_2.2.5) [2]	getpagesize(GLIBC_2.2.5) [4]	munlockall(GLIBC_2.2.5) [2]	setcontext(GLIBC_2.2.5) [2]	utime(GLIBC_2.2.5) [2]

dup2(GLIBC_2.2.5) [2]	getpgid(GLIBC_2.2.5) [2]	munmap(GLIBC_2.2.5) [2]	setegid(GLIBC_2.2.5) [2]	utimes(GLIBC_2.2.5) [2]
execl(GLIBC_2.2.5) [2]	getpgrp(GLIBC_2.2.5) [2]	nanosleep(GLIBC_2.2.5) [2]	seteuid(GLIBC_2.2.5) [2]	vfork(GLIBC_2.2.5) [2]
execle(GLIBC_2.2.5) [2]	getpid(GLIBC_2.2.5) [2]	nice(GLIBC_2.2.5) [2]	setgid(GLIBC_2.2.5) [2]	wait(GLIBC_2.2.5) [2]
execlp(GLIBC_2.2.5) [2]	getppid(GLIBC_2.2.5) [2]	open(GLIBC_2.2.5) [2]	setitimer(GLIBC_2.2.5) [2]	wait4(GLIBC_2.2.5) [1]
execv(GLIBC_2.2.5) [2]	getpriority(GLIBC_2.2.5) [2]	opendir(GLIBC_2.2.5) [2]	setpgid(GLIBC_2.2.5) [2]	waitpid(GLIBC_2.2.5) [1]
execve(GLIBC_2.2.5) [2]	getrlimit(GLIBC_2.2.5) [2]	pathconf(GLIBC_2.2.5) [2]	setpgrp(GLIBC_2.2.5) [2]	write(GLIBC_2.2.5) [2]
execvp(GLIBC_2.2.5) [2]	getrusage(GLIBC_2.2.5) [2]	pause(GLIBC_2.2.5) [2]	setpriority(GLIBC_2.2.5) [2]	writew(GLIBC_2.2.5) [2]
exit(GLIBC_2.2.5) [2]	getsid(GLIBC_2.2.5) [2]	pipe(GLIBC_2.2.5) [2]	setregid(GLIBC_2.2.5) [2]	
fchdir(GLIBC_2.2.5) [2]	getuid(GLIBC_2.2.5) [2]	poll(GLIBC_2.2.5) [2]	setreuid(GLIBC_2.2.5) [2]	

Referenced Specification(s)

[1]. this specification

[2]. ISO POSIX (2003)

[3]. Large File Support

[4]. SUSv2

## 11.2.3 Standard I/O

### 11.2.3.1 Interfaces for Standard I/O

An LSB conforming implementation shall provide the architecture specific functions for Standard I/O specified in Table 11-4, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-4 libc - Standard I/O Function Interfaces**

_IO_feof(GLIBC_2.2.5) [1]	fgetpos(GLIBC_2.2.5) [2]	fsetpos(GLIBC_2.2.5) [2]	putchar(GLIBC_2.2.5) [2]	sscanf(GLIBC_2.2.5) [1]
_IO_getc(GLIBC_2.2.5) [1]	fgets(GLIBC_2.2.5) [2]	ftell(GLIBC_2.2.5) [2]	putchar_unlocked(GLIBC_2.2.5) [2]	telldir(GLIBC_2.2.5) [2]
_IO_putc(GLIBC_2.2.5) [1]	fgetwc_unlocked(GLIBC_2.2.5) [1]	ftello(GLIBC_2.2.5) [2]	puts(GLIBC_2.2.5) [2]	tempnam(GLIBC_2.2.5) [2]
_IO_puts(GLIBC_2.2.5) [1]	fileno(GLIBC_2.2.5) [2]	fwrite(GLIBC_2.2.5) [2]	putw(GLIBC_2.2.5) [2]	ungetc(GLIBC_2.2.5) [2]

BC_2.2.5) [1]	_2.2.5) [2]	_2.2.5) [2]	2.2.5) [3]	C_2.2.5) [2]
asprintf(GLIBC_2.2.5) [1]	flockfile(GLIBC_2.2.5) [2]	getc(GLIBC_2.2.5) [2]	remove(GLIBC_2.2.5) [2]	vasprintf(GLIBC_2.2.5) [1]
clearerr(GLIBC_2.2.5) [2]	fopen(GLIBC_2.2.5) [2]	getc_unlocked(GLIBC_2.2.5) [2]	rewind(GLIBC_2.2.5) [2]	vdprintf(GLIBC_2.2.5) [1]
ctermid(GLIBC_2.2.5) [2]	fprintf(GLIBC_2.2.5) [2]	getchar(GLIBC_2.2.5) [2]	rewinddir(GLIBC_2.2.5) [2]	vfprintf(GLIBC_2.2.5) [2]
fclose(GLIBC_2.2.5) [2]	fputc(GLIBC_2.2.5) [2]	getchar_unlocked(GLIBC_2.2.5) [2]	scanf(GLIBC_2.2.5) [1]	vprintf(GLIBC_2.2.5) [2]
fdopen(GLIBC_2.2.5) [2]	fputs(GLIBC_2.2.5) [2]	getw(GLIBC_2.2.5) [3]	seekdir(GLIBC_2.2.5) [2]	vsnprintf(GLIBC_2.2.5) [2]
feof(GLIBC_2.2.5) [2]	fread(GLIBC_2.2.5) [2]	pclose(GLIBC_2.2.5) [2]	setbuf(GLIBC_2.2.5) [2]	vsprintf(GLIBC_2.2.5) [2]
ferror(GLIBC_2.2.5) [2]	freopen(GLIBC_2.2.5) [2]	popen(GLIBC_2.2.5) [2]	setbuffer(GLIBC_2.2.5) [1]	
fflush(GLIBC_2.2.5) [2]	fscanf(GLIBC_2.2.5) [1]	printf(GLIBC_2.2.5) [2]	setvbuf(GLIBC_2.2.5) [2]	
fflush_unlocked(GLIBC_2.2.5) [1]	fseek(GLIBC_2.2.5) [2]	putc(GLIBC_2.2.5) [2]	snprintf(GLIBC_2.2.5) [2]	
fgetc(GLIBC_2.2.5) [2]	fseeko(GLIBC_2.2.5) [2]	putc_unlocked(GLIBC_2.2.5) [2]	sprintf(GLIBC_2.2.5) [2]	

Referenced Specification(s)

[1]. this specification

[2]. ISO POSIX (2003)

[3]. SUSv2

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard I/O specified in Table 11-5, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-5 libc - Standard I/O Data Interfaces**

stderr(GLIBC_2.2.5) [1]	stdin(GLIBC_2.2.5) [1]	stdout(GLIBC_2.2.5) [1]		
-------------------------	------------------------	-------------------------	--	--

Referenced Specification(s)

[1]. ISO POSIX (2003)



## 11.2.4 Signal Handling

### 11.2.4.1 Interfaces for Signal Handling

An LSB conforming implementation shall provide the architecture specific functions for Signal Handling specified in Table 11-6, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-6 libc - Signal Handling Function Interfaces**

__libc_current _sigrtmax(GLIBC_2.2.5) [1]	sigaction(GLIBC_2.2.5) [2]	sighold(GLIBC_2.2.5) [2]	sigorset(GLIBC_2.2.5) [1]	sigset(GLIBC_2.2.5) [2]
__libc_current _sigrtmin(GLIBC_2.2.5) [1]	sigaddset(GLIBC_2.2.5) [2]	sigignore(GLIBC_2.2.5) [2]	sigpause(GLIBC_2.2.5) [2]	sigsuspend(GLIBC_2.2.5) [2]
__sigsetjmp(GLIBC_2.2.5) [1]	sigaltstack(GLIBC_2.2.5) [2]	siginterrupt(GLIBC_2.2.5) [2]	sigpending(GLIBC_2.2.5) [2]	sigtimedwait(GLIBC_2.2.5) [2]
__sysv_signal(GLIBC_2.2.5) [1]	sigandset(GLIBC_2.2.5) [1]	sigisemptyset(GLIBC_2.2.5) [1]	sigprocmask(GLIBC_2.2.5) [2]	sigwait(GLIBC_2.2.5) [2]
bsd_signal(GLIBC_2.2.5) [2]	sigdelset(GLIBC_2.2.5) [2]	sigismember(GLIBC_2.2.5) [2]	sigqueue(GLIBC_2.2.5) [2]	sigwaitinfo(GLIBC_2.2.5) [2]
psignal(GLIBC_2.2.5) [1]	sigemptyset(GLIBC_2.2.5) [2]	siglongjmp(GLIBC_2.2.5) [2]	sigrelse(GLIBC_2.2.5) [2]	
raise(GLIBC_2.2.5) [2]	sigfillset(GLIBC_2.2.5) [2]	signal(GLIBC_2.2.5) [2]	sigreturn(GLIBC_2.2.5) [1]	

*Referenced Specification(s)*

[1]. this specification

[2]. ISO POSIX (2003)

An LSB conforming implementation shall provide the architecture specific data interfaces for Signal Handling specified in Table 11-7, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-7 libc - Signal Handling Data Interfaces**

__sys_siglist(GLIBC_2.3.3) [1]				
--------------------------------	--	--	--	--

*Referenced Specification(s)*

[1]. this specification

## 11.2.5 Localization Functions

### 11.2.5.1 Interfaces for Localization Functions

An LSB conforming implementation shall provide the architecture specific functions for Localization Functions specified in Table 11-8, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-8 libc - Localization Functions Function Interfaces**

bind_textdomain_codeset(GLIBC_2.2.5) [1]	catopen(GLIBC_2.2.5) [2]	dngettext(GLIBC_2.2.5) [1]	iconv_open(GLIBC_2.2.5) [2]	setlocale(GLIBC_2.2.5) [2]
bindtextdomain(GLIBC_2.2.5) [1]	dcgettext(GLIBC_2.2.5) [1]	gettext(GLIBC_2.2.5) [1]	localeconv(GLIBC_2.2.5) [2]	textdomain(GLIBC_2.2.5) [1]
catclose(GLIBC_2.2.5) [2]	dcngettext(GLIBC_2.2.5) [1]	iconv(GLIBC_2.2.5) [2]	ngettext(GLIBC_2.2.5) [1]	
catgets(GLIBC_2.2.5) [2]	dgettext(GLIBC_2.2.5) [1]	iconv_close(GLIBC_2.2.5) [2]	nl_langinfo(GLIBC_2.2.5) [2]	

*Referenced Specification(s)*

[1]. this specification

[2]. ISO POSIX (2003)

An LSB conforming implementation shall provide the architecture specific data interfaces for Localization Functions specified in Table 11-9, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-9 libc - Localization Functions Data Interfaces**

_nl_msg_cat_cntr(GLIBC_2.2.5) [1]				
-----------------------------------	--	--	--	--

*Referenced Specification(s)*

[1]. this specification

## 11.2.6 Socket Interface

### 11.2.6.1 Interfaces for Socket Interface

An LSB conforming implementation shall provide the architecture specific functions for Socket Interface specified in Table 11-10, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-10 libc - Socket Interface Function Interfaces**

__h_errno_location(GLIBC_2.2.5) [1]	gethostname(GLIBC_2.2.5)	if_nameindex(GLIBC_2.2.5)	send(GLIBC_2.2.5) [2]	socket(GLIBC_2.2.5) [2]
-------------------------------------	--------------------------	---------------------------	-----------------------	-------------------------

2.2.5) [1]	[2]	[2]		
accept(GLIBC_2.2.5) [2]	getpeername(GLIBC_2.2.5) [2]	if_nametoindex(GLIBC_2.2.5) [2]	sendmsg(GLIBC_2.2.5) [2]	socketpair(GLIBC_2.2.5) [2]
bind(GLIBC_2.2.5) [2]	getsockname(GLIBC_2.2.5) [2]	listen(GLIBC_2.2.5) [2]	sendto(GLIBC_2.2.5) [2]	
bindresvport(GLIBC_2.2.5) [1]	getsockopt(GLIBC_2.2.5) [1]	recv(GLIBC_2.2.5) [2]	setsockopt(GLIBC_2.2.5) [1]	
connect(GLIBC_2.2.5) [2]	if_freenameindex(GLIBC_2.2.5) [2]	recvfrom(GLIBC_2.2.5) [2]	shutdown(GLIBC_2.2.5) [2]	
gethostid(GLIBC_2.2.5) [2]	if_indextoname(GLIBC_2.2.5) [2]	recvmsg(GLIBC_2.2.5) [2]	socketatmark(GLIBC_2.2.5) [2]	

Referenced Specification(s)

[1]. this specification

[2]. ISO POSIX (2003)

## 11.2.7 Wide Characters

### 11.2.7.1 Interfaces for Wide Characters

An LSB conforming implementation shall provide the architecture specific functions for Wide Characters specified in Table 11-11, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-11 libc - Wide Characters Function Interfaces**

__wctod_internale(GLIBC_2.2.5) [1]	mbsinit(GLIBC_2.2.5) [2]	vwscanf(GLIBC_2.2.5) [1]	wcsnlen(GLIBC_2.2.5) [1]	wcstoumax(GLIBC_2.2.5) [2]
__wctof_internale(GLIBC_2.2.5) [1]	mbsrtowcs(GLIBC_2.2.5) [1]	wcpcpy(GLIBC_2.2.5) [1]	wcsnrtombs(GLIBC_2.2.5) [1]	wcstouq(GLIBC_2.2.5) [1]
__wctol_internale(GLIBC_2.2.5) [1]	mbsrtowcs(GLIBC_2.2.5) [2]	wcpncpy(GLIBC_2.2.5) [1]	wcspbrk(GLIBC_2.2.5) [2]	wcswcs(GLIBC_2.2.5) [2]
__wctold_internale(GLIBC_2.2.5) [1]	mbstowcs(GLIBC_2.2.5) [2]	wcrtomb(GLIBC_2.2.5) [2]	wcsrchr(GLIBC_2.2.5) [2]	wcswidth(GLIBC_2.2.5) [2]
__wctoul_internale(GLIBC_2.2.5) [1]	mbtowc(GLIBC_2.2.5) [2]	wcscasecmp(GLIBC_2.2.5) [1]	wcsrtombs(GLIBC_2.2.5) [2]	wcsxfrm(GLIBC_2.2.5) [2]
btowc(GLIBC_2.2.5) [1]	putwc(GLIBC_2.2.5) [2]	wcscat(GLIBC_2.2.5) [2]	wcsspn(GLIBC_2.2.5) [2]	wctob(GLIBC_2.2.5) [2]

_2.2.5) [2]	_2.2.5) [2]	_2.2.5) [2]	C_2.2.5) [2]	_2.2.5) [2]
fgetwc(GLIBC_2.2.5) [2]	putwchar(GLIBC_2.2.5) [2]	wcschr(GLIBC_2.2.5) [2]	wcsstr(GLIBC_2.2.5) [2]	wctomb(GLIBC_2.2.5) [2]
fgetws(GLIBC_2.2.5) [2]	swprintf(GLIBC_2.2.5) [2]	wcscmp(GLIBC_2.2.5) [2]	wcstod(GLIBC_2.2.5) [2]	wctrans(GLIBC_2.2.5) [2]
fputwc(GLIBC_2.2.5) [2]	swscanf(GLIBC_2.2.5) [1]	wscoll(GLIBC_2.2.5) [2]	wcstof(GLIBC_2.2.5) [2]	wctype(GLIBC_2.2.5) [2]
fputws(GLIBC_2.2.5) [2]	towctrans(GLIBC_2.2.5) [2]	wscpy(GLIBC_2.2.5) [2]	wcstoimax(GLIBC_2.2.5) [2]	wcwidth(GLIBC_2.2.5) [2]
fwide(GLIBC_2.2.5) [2]	towlower(GLIBC_2.2.5) [2]	wscspn(GLIBC_2.2.5) [2]	wcstok(GLIBC_2.2.5) [2]	wmemchr(GLIBC_2.2.5) [2]
fwprintf(GLIBC_2.2.5) [2]	towupper(GLIBC_2.2.5) [2]	wcsdup(GLIBC_2.2.5) [1]	wcstol(GLIBC_2.2.5) [2]	wmemcmp(GLIBC_2.2.5) [2]
fwscanf(GLIBC_2.2.5) [1]	ungetwc(GLIBC_2.2.5) [2]	wcsftime(GLIBC_2.2.5) [2]	wcstold(GLIBC_2.2.5) [2]	wmemcpy(GLIBC_2.2.5) [2]
getwc(GLIBC_2.2.5) [2]	vwprintf(GLIBC_2.2.5) [2]	wcslen(GLIBC_2.2.5) [2]	wcstoll(GLIBC_2.2.5) [2]	wmemmove(GLIBC_2.2.5) [2]
getwchar(GLIBC_2.2.5) [2]	vwscanf(GLIBC_2.2.5) [1]	wcsncasecmp(GLIBC_2.2.5) [1]	wcstombs(GLIBC_2.2.5) [2]	wmemset(GLIBC_2.2.5) [2]
mblen(GLIBC_2.2.5) [2]	vswprintf(GLIBC_2.2.5) [2]	wcsncat(GLIBC_2.2.5) [2]	wcstoq(GLIBC_2.2.5) [1]	wprintf(GLIBC_2.2.5) [2]
mbrlen(GLIBC_2.2.5) [2]	vswscanf(GLIBC_2.2.5) [1]	wcsncmp(GLIBC_2.2.5) [2]	wcstoul(GLIBC_2.2.5) [2]	wscanf(GLIBC_2.2.5) [1]
mbrtowc(GLIBC_2.2.5) [2]	vwprintf(GLIBC_2.2.5) [2]	wcsncpy(GLIBC_2.2.5) [2]	wcstoull(GLIBC_2.2.5) [2]	

Referenced Specification(s)

[1]. this specification

[2]. ISO POSIX (2003)

## 11.2.8 String Functions

### 11.2.8.1 Interfaces for String Functions

An LSB conforming implementation shall provide the architecture specific functions for String Functions specified in Table 11-12, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-12 libc - String Functions Function Interfaces**

__mempcpy(	bzero(GLIBC_	strcasestr(GLI	strncat(GLIB	strtok(GLIBC
------------	--------------	----------------	--------------	--------------

GLIBC_2.2.5) [1]	2.2.5) [2]	BC_2.2.5) [1]	C_2.2.5) [2]	_2.2.5) [2]
__rawmemchr(GLIBC_2.2.5) [1]	ffs(GLIBC_2.2.5) [2]	strcat(GLIBC_2.2.5) [2]	strncmp(GLIBC_2.2.5) [2]	strtok_r(GLIBC_2.2.5) [2]
__stpcpy(GLIBC_2.2.5) [1]	index(GLIBC_2.2.5) [2]	strchr(GLIBC_2.2.5) [2]	strncpy(GLIBC_2.2.5) [2]	strtol(GLIBC_2.2.5) [2]
__strdup(GLIBC_2.2.5) [1]	memcpy(GLIBC_2.2.5) [2]	strcmp(GLIBC_2.2.5) [2]	strndup(GLIBC_2.2.5) [1]	strtoll(GLIBC_2.2.5) [2]
__strtod_internal(GLIBC_2.2.5) [1]	memchr(GLIBC_2.2.5) [2]	strcoll(GLIBC_2.2.5) [2]	strnlen(GLIBC_2.2.5) [1]	strtoq(GLIBC_2.2.5) [1]
__strtof_internal(GLIBC_2.2.5) [1]	memcmp(GLIBC_2.2.5) [2]	strcpy(GLIBC_2.2.5) [2]	strpbrk(GLIBC_2.2.5) [2]	strtoull(GLIBC_2.2.5) [2]
__strtok_r(GLIBC_2.2.5) [1]	memcpy(GLIBC_2.2.5) [2]	strcspn(GLIBC_2.2.5) [2]	strptime(GLIBC_2.2.5) [1]	strtoumax(GLIBC_2.2.5) [2]
__strtol_internal(GLIBC_2.2.5) [1]	memmove(GLIBC_2.2.5) [2]	strdup(GLIBC_2.2.5) [2]	strrchr(GLIBC_2.2.5) [2]	strtouq(GLIBC_2.2.5) [1]
__strtol_internal(GLIBC_2.2.5) [1]	memchr(GLIBC_2.2.5) [1]	strerror(GLIBC_2.2.5) [2]	strsep(GLIBC_2.2.5) [1]	strxfrm(GLIBC_2.2.5) [2]
__strtoll_internal(GLIBC_2.2.5) [1]	memset(GLIBC_2.2.5) [2]	strerror_r(GLIBC_2.2.5) [1]	strsignal(GLIBC_2.2.5) [1]	swab(GLIBC_2.2.5) [2]
__strtoul_internal(GLIBC_2.2.5) [1]	rindex(GLIBC_2.2.5) [2]	strfmon(GLIBC_2.2.5) [2]	strspn(GLIBC_2.2.5) [2]	
__strtoull_internal(GLIBC_2.2.5) [1]	stpcpy(GLIBC_2.2.5) [1]	strftime(GLIBC_2.2.5) [2]	strstr(GLIBC_2.2.5) [2]	
bcmp(GLIBC_2.2.5) [2]	stpcpy(GLIBC_2.2.5) [1]	strlen(GLIBC_2.2.5) [2]	strtof(GLIBC_2.2.5) [2]	
bcopy(GLIBC_2.2.5) [2]	strcasecmp(GLIBC_2.2.5) [2]	strncasecmp(GLIBC_2.2.5) [2]	strtoimax(GLIBC_2.2.5) [2]	

*Referenced Specification(s)*

[1]. this specification

[2]. ISO POSIX (2003)

## 11.2.9 IPC Functions

### 11.2.9.1 Interfaces for IPC Functions

An LSB conforming implementation shall provide the architecture specific functions for IPC Functions specified in Table 11-13, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-13 libc - IPC Functions Function Interfaces**

ftok(GLIBC_2.2.5) [1]	msgrcv(GLIBC_2.2.5) [1]	semget(GLIBC_2.2.5) [1]	shmctl(GLIBC_2.2.5) [1]	
msgctl(GLIBC_2.2.5) [1]	msgsnd(GLIBC_2.2.5) [1]	semop(GLIBC_2.2.5) [1]	shmdt(GLIBC_2.2.5) [1]	
msgget(GLIBC_2.2.5) [1]	semctl(GLIBC_2.2.5) [1]	shmat(GLIBC_2.2.5) [1]	shmget(GLIBC_2.2.5) [1]	

*Referenced Specification(s)*

[1]. ISO POSIX (2003)

## 11.2.10 Regular Expressions

### 11.2.10.1 Interfaces for Regular Expressions

An LSB conforming implementation shall provide the architecture specific functions for Regular Expressions specified in Table 11-14, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-14 libc - Regular Expressions Function Interfaces**

regcomp(GLIBC_2.2.5) [1]	regerror(GLIBC_2.2.5) [1]	regexexec(GLIBC_2.3.4) [2]	regfree(GLIBC_2.2.5) [1]	
--------------------------	---------------------------	----------------------------	--------------------------	--

*Referenced Specification(s)*

[1]. ISO POSIX (2003)

[2]. this specification

## 11.2.11 Character Type Functions

### 11.2.11.1 Interfaces for Character Type Functions

An LSB conforming implementation shall provide the architecture specific functions for Character Type Functions specified in Table 11-15, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-15 libc - Character Type Functions Function Interfaces**

__ctype_get_mb_cur_max(GLIBC_2.2.5) [1]	isdigit(GLIBC_2.2.5) [2]	iswalnum(GLIBC_2.2.5) [2]	iswlower(GLIBC_2.2.5) [2]	toascii(GLIBC_2.2.5) [2]
_tolower(GLIBC_2.2.5) [2]	isgraph(GLIBC_2.2.5) [2]	iswalpha(GLIBC_2.2.5) [2]	iswprint(GLIBC_2.2.5) [2]	tolower(GLIBC_2.2.5) [2]

<code>_toupper</code> (GLIBC_2.2.5) [2]	<code>islower</code> (GLIBC_2.2.5) [2]	<code>iswblank</code> (GLIBC_2.2.5) [2]	<code>iswpunct</code> (GLIBC_2.2.5) [2]	<code>toupper</code> (GLIBC_2.2.5) [2]
<code>isalnum</code> (GLIBC_2.2.5) [2]	<code>isprint</code> (GLIBC_2.2.5) [2]	<code>iswcntrl</code> (GLIBC_2.2.5) [2]	<code>iswspace</code> (GLIBC_2.2.5) [2]	
<code>isalpha</code> (GLIBC_2.2.5) [2]	<code>ispunct</code> (GLIBC_2.2.5) [2]	<code>iswctype</code> (GLIBC_2.2.5) [2]	<code>iswupper</code> (GLIBC_2.2.5) [2]	
<code>isascii</code> (GLIBC_2.2.5) [2]	<code>isspace</code> (GLIBC_2.2.5) [2]	<code>iswdigit</code> (GLIBC_2.2.5) [2]	<code>iswxdigit</code> (GLIBC_2.2.5) [2]	
<code>iscntrl</code> (GLIBC_2.2.5) [2]	<code>isupper</code> (GLIBC_2.2.5) [2]	<code>iswgraph</code> (GLIBC_2.2.5) [2]	<code>isxdigit</code> (GLIBC_2.2.5) [2]	

*Referenced Specification(s)*

[1]. this specification

[2]. ISO POSIX (2003)

## 11.2.12 Time Manipulation

### 11.2.12.1 Interfaces for Time Manipulation

An LSB conforming implementation shall provide the architecture specific functions for Time Manipulation specified in Table 11-16, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-16 libc - Time Manipulation Function Interfaces**

<code>adjtime</code> (GLIBC_2.2.5) [1]	<code>ctime</code> (GLIBC_2.2.5) [2]	<code>gmtime</code> (GLIBC_2.2.5) [2]	<code>localtime_r</code> (GLIBC_2.2.5) [2]	<code>ualarm</code> (GLIBC_2.2.5) [2]
<code>asctime</code> (GLIBC_2.2.5) [2]	<code>ctime_r</code> (GLIBC_2.2.5) [2]	<code>gmtime_r</code> (GLIBC_2.2.5) [2]	<code>mktime</code> (GLIBC_2.2.5) [2]	
<code>asctime_r</code> (GLIBC_2.2.5) [2]	<code>difftime</code> (GLIBC_2.2.5) [2]	<code>localtime</code> (GLIBC_2.2.5) [2]	<code>tzset</code> (GLIBC_2.2.5) [2]	

*Referenced Specification(s)*

[1]. this specification

[2]. ISO POSIX (2003)

An LSB conforming implementation shall provide the architecture specific data interfaces for Time Manipulation specified in Table 11-17, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-17 libc - Time Manipulation Data Interfaces**

<code>__daylight</code> (GLIBC_2.2.5) [1]	<code>__tzname</code> (GLIBC_2.2.5) [1]	<code>timezone</code> (GLIBC_2.2.5) [2]		
<code>__timezone</code> (GLIBC_2.2.5) [1]	<code>daylight</code> (GLIBC_2.2.5) [2]	<code>tzname</code> (GLIBC_2.2.5) [2]		

*Referenced Specification(s)*

[1]. this specification

[2]. ISO POSIX (2003)

**11.2.13 Terminal Interface Functions****11.2.13.1 Interfaces for Terminal Interface Functions**

An LSB conforming implementation shall provide the architecture specific functions for Terminal Interface Functions specified in Table 11-18, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-18 libc - Terminal Interface Functions Function Interfaces**

cfgetispeed(G LIBC_2.2.5) [1]	cfsetispeed(G LIBC_2.2.5) [1]	tcdrain(GLIB C_2.2.5) [1]	tcgetattr(GLIB C_2.2.5) [1]	tcsendbreak( GLIBC_2.2.5) [1]
cfgetospeed( GLIBC_2.2.5) [1]	cfsetospeed(G LIBC_2.2.5) [1]	tcflow(GLIBC _2.2.5) [1]	tcgetpgrp(GLI BC_2.2.5) [1]	tcsetattr(GLIB C_2.2.5) [1]
cfmakeraw(G LIBC_2.2.5) [2]	cfsetspeed(GL IBC_2.2.5) [2]	tcflush(GLIB C_2.2.5) [1]	tcgetsid(GLIB C_2.2.5) [1]	tcsetpgrp(GLI BC_2.2.5) [1]

*Referenced Specification(s)*

[1]. ISO POSIX (2003)

[2]. this specification

**11.2.14 System Database Interface****11.2.14.1 Interfaces for System Database Interface**

An LSB conforming implementation shall provide the architecture specific functions for System Database Interface specified in Table 11-19, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-19 libc - System Database Interface Function Interfaces**

endgrent(GLI BC_2.2.5) [1]	getgrgid_r(G LIBC_2.2.5) [1]	getprotoent(G LIBC_2.2.5) [1]	getservent(GL IBC_2.2.5) [1]	setgroups(GL IBC_2.2.5) [2]
endprotoent( GLIBC_2.2.5) [1]	getgrnam(GLI BC_2.2.5) [1]	getpwent(GLI BC_2.2.5) [1]	gettutent(GLIB C_2.2.5) [2]	setprotoent(G LIBC_2.2.5) [1]
endpwent(GL IBC_2.2.5) [1]	getgrnam_r(G LIBC_2.2.5) [1]	getpwnam(G LIBC_2.2.5) [1]	gettutent_r(GL IBC_2.2.5) [2]	setpwent(GLI BC_2.2.5) [1]
endservent(G LIBC_2.2.5) [1]	getgrouplist( GLIBC_2.2.5) [2]	getpwnam_r( GLIBC_2.2.5) [1]	gettutxent(GLI BC_2.2.5) [1]	setservent(GL IBC_2.2.5) [1]



endutent(GLIBC_2.2.5) [3]	gethostbyaddr(GLIBC_2.2.5) [1]	getpwuid(GLIBC_2.2.5) [1]	getutxid(GLIBC_2.2.5) [1]	setutent(GLIBC_2.2.5) [2]
endutxent(GLIBC_2.2.5) [1]	gethostbyname(GLIBC_2.2.5) [1]	getpwuid_r(GLIBC_2.2.5) [1]	getutxline(GLIBC_2.2.5) [1]	setutxent(GLIBC_2.2.5) [1]
getgrent(GLIBC_2.2.5) [1]	getprotobyname(GLIBC_2.2.5) [1]	getservbyname(GLIBC_2.2.5) [1]	pututxline(GLIBC_2.2.5) [1]	utmpname(GLIBC_2.2.5) [2]
getgrgid(GLIBC_2.2.5) [1]	getprotobynumber(GLIBC_2.2.5) [1]	getservbyport(GLIBC_2.2.5) [1]	setgrent(GLIBC_2.2.5) [1]	

*Referenced Specification(s)*

[1]. ISO POSIX (2003)

[2]. this specification

[3]. SUSv2

## 11.2.15 Language Support

### 11.2.15.1 Interfaces for Language Support

An LSB conforming implementation shall provide the architecture specific functions for Language Support specified in Table 11-20, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-20 libc - Language Support Function Interfaces**

__libc_start_main(GLIBC_2.2.5) [1]				
------------------------------------	--	--	--	--

*Referenced Specification(s)*

[1]. this specification

## 11.2.16 Large File Support

### 11.2.16.1 Interfaces for Large File Support

An LSB conforming implementation shall provide the architecture specific functions for Large File Support specified in Table 11-21, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-21 libc - Large File Support Function Interfaces**

__fxstat64(GLIBC_2.2.5) [1]	fopen64(GLIBC_2.2.5) [2]	ftello64(GLIBC_2.2.5) [2]	mkstemp64(GLIBC_2.2.5) [2]	tmpfile64(GLIBC_2.2.5) [2]
__lxstat64(GLIBC_2.2.5) [1]	freopen64(GLIBC_2.2.5) [2]	ftruncate64(GLIBC_2.2.5) [2]	mmap64(GLIBC_2.2.5) [2]	truncate64(GLIBC_2.2.5) [2]

__xstat64(GLIBC_2.2.5) [1]	fseeko64(GLIBC_2.2.5) [2]	ftw64(GLIBC_2.2.5) [2]	nftw64(GLIBC_2.3.3) [2]	
creat64(GLIBC_2.2.5) [2]	fsetpos64(GLIBC_2.2.5) [2]	getrlimit64(GLIBC_2.2.5) [2]	readdir64(GLIBC_2.2.5) [2]	
fgetpos64(GLIBC_2.2.5) [2]	fstatvfs64(GLIBC_2.2.5) [2]	lockf64(GLIBC_2.2.5) [2]	statvfs64(GLIBC_2.2.5) [2]	

*Referenced Specification(s)*

[1]. this specification

[2]. Large File Support

## 11.2.17 Standard Library

### 11.2.17.1 Interfaces for Standard Library

An LSB conforming implementation shall provide the architecture specific functions for Standard Library specified in Table 11-22, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-22 libc - Standard Library Function Interfaces**

_Exit(GLIBC_2.2.5) [1]	dirname(GLIBC_2.2.5) [1]	gettimeofday(GLIBC_2.2.5) [1]	lrnd48(GLIBC_2.2.5) [1]	srand(GLIBC_2.2.5) [1]
__assert_fail(GLIBC_2.2.5) [2]	div(GLIBC_2.2.5) [1]	glob(GLIBC_2.2.5) [1]	lsearch(GLIBC_2.2.5) [1]	srand48(GLIBC_2.2.5) [1]
__cxa_atexit(GLIBC_2.2.5) [2]	drand48(GLIBC_2.2.5) [1]	glob64(GLIBC_2.2.5) [2]	makecontext(GLIBC_2.2.5) [1]	srandom(GLIBC_2.2.5) [1]
__errno_location(GLIBC_2.2.5) [2]	ecvt(GLIBC_2.2.5) [1]	globfree(GLIBC_2.2.5) [1]	malloc(GLIBC_2.2.5) [1]	strtod(GLIBC_2.2.5) [1]
__fpending(GLIBC_2.2.5) [2]	erand48(GLIBC_2.2.5) [1]	globfree64(GLIBC_2.2.5) [2]	memmem(GLIBC_2.2.5) [2]	strtol(GLIBC_2.2.5) [1]
__getpagesize(GLIBC_2.2.5) [2]	err(GLIBC_2.2.5) [2]	grantpt(GLIBC_2.2.5) [1]	mkstemp(GLIBC_2.2.5) [1]	strtoul(GLIBC_2.2.5) [1]
__isinf(GLIBC_2.2.5) [2]	error(GLIBC_2.2.5) [2]	hcreate(GLIBC_2.2.5) [1]	mktemp(GLIBC_2.2.5) [1]	swapcontext(GLIBC_2.2.5) [1]
__isinf(GLIBC_2.2.5) [2]	errx(GLIBC_2.2.5) [2]	hdestroy(GLIBC_2.2.5) [1]	mrnd48(GLIBC_2.2.5) [1]	syslog(GLIBC_2.2.5) [1]
__isnfl(GLIBC_2.2.5) [2]	fcvt(GLIBC_2.2.5) [1]	hsearch(GLIBC_2.2.5) [1]	nftw(GLIBC_2.3.3) [1]	system(GLIBC_2.2.5) [2]

<code>__isnan</code> (GLIBC_2.2.5) [2]	<code>fntmsg</code> (GLIBC_2.2.5) [1]	<code>htonl</code> (GLIBC_2.2.5) [1]	<code>nrand48</code> (GLIBC_2.2.5) [1]	<code>tdelete</code> (GLIBC_2.2.5) [1]
<code>__isnanf</code> (GLIBC_2.2.5) [2]	<code>fnmatch</code> (GLIBC_2.2.5) [1]	<code>htons</code> (GLIBC_2.2.5) [1]	<code>ntohl</code> (GLIBC_2.2.5) [1]	<code>tfind</code> (GLIBC_2.2.5) [1]
<code>__isnanl</code> (GLIBC_2.2.5) [2]	<code>fpathconf</code> (GLIBC_2.2.5) [1]	<code>imaxabs</code> (GLIBC_2.2.5) [1]	<code>ntohs</code> (GLIBC_2.2.5) [1]	<code>tmpfile</code> (GLIBC_2.2.5) [1]
<code>__sysconf</code> (GLIBC_2.2.5) [2]	<code>free</code> (GLIBC_2.2.5) [1]	<code>imaxdiv</code> (GLIBC_2.2.5) [1]	<code>openlog</code> (GLIBC_2.2.5) [1]	<code>tmpnam</code> (GLIBC_2.2.5) [1]
<code>_exit</code> (GLIBC_2.2.5) [1]	<code>freeaddrinfo</code> (GLIBC_2.2.5) [1]	<code>inet_addr</code> (GLIBC_2.2.5) [1]	<code>perror</code> (GLIBC_2.2.5) [1]	<code>tsearch</code> (GLIBC_2.2.5) [1]
<code>_longjmp</code> (GLIBC_2.2.5) [1]	<code>ftrylockfile</code> (GLIBC_2.2.5) [1]	<code>inet_ntoa</code> (GLIBC_2.2.5) [1]	<code>posix_memalign</code> (GLIBC_2.2.5) [1]	<code>ttynam</code> (GLIBC_2.2.5) [1]
<code>_setjmp</code> (GLIBC_2.2.5) [1]	<code>ftw</code> (GLIBC_2.2.5) [1]	<code>inet_ntop</code> (GLIBC_2.2.5) [1]	<code>posix_openpt</code> (GLIBC_2.2.5) [1]	<code>ttynam_r</code> (GLIBC_2.2.5) [1]
<code>a64l</code> (GLIBC_2.2.5) [1]	<code>funlockfile</code> (GLIBC_2.2.5) [1]	<code>inet_pton</code> (GLIBC_2.2.5) [1]	<code>ptsname</code> (GLIBC_2.2.5) [1]	<code>twalk</code> (GLIBC_2.2.5) [1]
<code>abort</code> (GLIBC_2.2.5) [1]	<code>gai_strerror</code> (GLIBC_2.2.5) [1]	<code>initstate</code> (GLIBC_2.2.5) [1]	<code>putenv</code> (GLIBC_2.2.5) [1]	<code>unlockpt</code> (GLIBC_2.2.5) [1]
<code>abs</code> (GLIBC_2.2.5) [1]	<code>gcvt</code> (GLIBC_2.2.5) [1]	<code>insque</code> (GLIBC_2.2.5) [1]	<code>qsort</code> (GLIBC_2.2.5) [1]	<code>unsetenv</code> (GLIBC_2.2.5) [1]
<code>atof</code> (GLIBC_2.2.5) [1]	<code>getaddrinfo</code> (GLIBC_2.2.5) [1]	<code>isatty</code> (GLIBC_2.2.5) [1]	<code>rand</code> (GLIBC_2.2.5) [1]	<code>usleep</code> (GLIBC_2.2.5) [1]
<code>atoi</code> (GLIBC_2.2.5) [1]	<code>getcwd</code> (GLIBC_2.2.5) [1]	<code>isblank</code> (GLIBC_2.2.5) [1]	<code>rand_r</code> (GLIBC_2.2.5) [1]	<code>verrx</code> (GLIBC_2.2.5) [2]
<code>atol</code> (GLIBC_2.2.5) [1]	<code>getdate</code> (GLIBC_2.2.5) [1]	<code>jrand48</code> (GLIBC_2.2.5) [1]	<code>random</code> (GLIBC_2.2.5) [1]	<code>vfscanf</code> (GLIBC_2.2.5) [2]
<code>atoll</code> (GLIBC_2.2.5) [1]	<code>getenv</code> (GLIBC_2.2.5) [1]	<code>l64a</code> (GLIBC_2.2.5) [1]	<code>realloc</code> (GLIBC_2.2.5) [1]	<code>vscanf</code> (GLIBC_2.2.5) [2]
<code>basename</code> (GLIBC_2.2.5) [1]	<code>getlogin</code> (GLIBC_2.2.5) [1]	<code>labs</code> (GLIBC_2.2.5) [1]	<code>realpath</code> (GLIBC_2.3) [1]	<code>vsscanf</code> (GLIBC_2.2.5) [2]
<code>bsearch</code> (GLIBC_2.2.5) [1]	<code>getlogin_r</code> (GLIBC_2.2.5) [1]	<code>lcong48</code> (GLIBC_2.2.5) [1]	<code>remque</code> (GLIBC_2.2.5) [1]	<code>vsyslog</code> (GLIBC_2.2.5) [2]
<code>calloc</code> (GLIBC_2.2.5) [1]	<code>getnameinfo</code> (GLIBC_2.2.5) [1]	<code>ldiv</code> (GLIBC_2.2.5) [1]	<code>seed48</code> (GLIBC_2.2.5) [1]	<code>warn</code> (GLIBC_2.2.5) [2]
<code>closelog</code> (GLIBC)	<code>getopt</code> (GLIBC)	<code>lfind</code> (GLIBC_2.2.5) [1]	<code>setenv</code> (GLIBC)	<code>warnx</code> (GLIBC)

C_2.2.5) [1]	_2.2.5) [2]	2.2.5) [1]	_2.2.5) [1]	_2.2.5) [2]
confstr(GLIB C_2.2.5) [1]	getopt_long(GLIBC_2.2.5) [2]	llabs(GLIBC_2.2.5) [1]	sethostname(GLIBC_2.2.5) [2]	wordexp(GLIBC_2.2.5) [1]
cuserid(GLIB C_2.2.5) [3]	getopt_long_only(GLIBC_2.2.5) [2]	lldiv(GLIBC_2.2.5) [1]	setlogmask(GLIBC_2.2.5) [1]	wordfree(GLIBC_2.2.5) [1]
daemon(GLIB C_2.2.5) [2]	getsubopt(GLIBC_2.2.5) [1]	longjmp(GLIBC_2.2.5) [1]	setstate(GLIB C_2.2.5) [1]	

*Referenced Specification(s)*

[1]. ISO POSIX (2003)

[2]. this specification

[3]. SUSv2

An LSB conforming implementation shall provide the architecture specific data interfaces for Standard Library specified in Table 11-23, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-23 libc - Standard Library Data Interfaces**

__environ(GLIBC_2.2.5) [1]	_sys_errlist(GLIBC_2.3) [1]	getdate_err(GLIBC_2.2.5) [2]	opterr(GLIBC_2.2.5) [2]	optopt(GLIBC_2.2.5) [2]
_environ(GLIBC_2.2.5) [1]	environ(GLIB C_2.2.5) [2]	optarg(GLIBC_2.2.5) [2]	optind(GLIBC_2.2.5) [2]	

*Referenced Specification(s)*

[1]. this specification

[2]. ISO POSIX (2003)

## 11.3 Data Definitions for libc

This section defines global identifiers and their values that are associated with interfaces contained in libc. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content.

These definitions are intended to supplement those provided in the referenced underlying specifications.

This specification uses ISO/IEC 9899 C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 11.3.1 errno.h

```
#define EDEADLOCK          EDEADLK
```

### 11.3.2 fcntl.h

```
#define F_GETLK64      5
#define F_SETLK64      6
#define F_SETLKW64     7
```

### 11.3.3 inttypes.h

```
typedef long int intmax_t;
typedef unsigned long int uintptr_t;
typedef unsigned long int uintmax_t;
typedef unsigned long int uint64_t;
```

### 11.3.4 limits.h

```
#define LONG_MAX      0x7FFFFFFFFFFFFFFFL
#define ULONG_MAX     0xFFFFFFFFFFFFFFFFUL

#define CHAR_MAX      127
#define CHAR_MIN      SCHAR_MIN

#define PTHREAD_STACK_MIN 16384
```

### 11.3.5 setjmp.h

```
typedef long int __jmp_buf[8];
```

### 11.3.6 signal.h

```
#define SIGEV_PAD_SIZE ((SIGEV_MAX_SIZE/sizeof(int))-4)
#define SI_PAD_SIZE    ((SI_MAX_SIZE/sizeof(int))-4)

struct sigaction
{
    union
    {
        {
            sighandler_t _sa_handler;
            void (*_sa_sigaction) (int, siginfo_t *, void *);
        }
        __sigaction_handler;
        sigset_t sa_mask;
        int sa_flags;
        void (*sa_restorer) (void);
    }
};

#define MINSIGSTKSZ 2048
#define SIGSTKSZ 8192

struct _fpxreg
{
    unsigned short significand[4];
    unsigned short exponent;
    unsigned short padding[3];
};

struct _xmmreg
{
```

```

    uint32_t element[4];
}
;

struct _fpstate
{
    uint16_t cwd;
    uint16_t swd;
    uint16_t ftw;
    uint16_t fop;
    uint64_t rip;
    uint64_t rdp;
    uint32_t mxcsr;
    uint32_t mxcr_mask;
    struct _fpxreg _st[8];
    struct _xmmreg _xmm[16];
    uint32_t padding[24];
}
;

struct sigcontext
{
    unsigned long int r8;
    unsigned long int r9;
    unsigned long int r10;
    unsigned long int r11;
    unsigned long int r12;
    unsigned long int r13;
    unsigned long int r14;
    unsigned long int r15;
    unsigned long int rdi;
    unsigned long int rsi;
    unsigned long int rbp;
    unsigned long int rbx;
    unsigned long int rdx;
    unsigned long int rax;
    unsigned long int rcx;
    unsigned long int rsp;
    unsigned long int rip;
    unsigned long int eflags;
    unsigned short cs;
    unsigned short gs;
    unsigned short fs;
    unsigned short __pad0;
    unsigned long int err;
    unsigned long int trapno;
    unsigned long int oldmask;
    unsigned long int cr2;
    struct _fpstate *fpstate;
    unsigned long int __reserved1[8];
}
;

```

### 11.3.7 stddef.h

```

typedef long int ptrdiff_t;
typedef unsigned long int size_t;

```

### 11.3.8 stdio.h

```

#define __IO_FILE_SIZE 216

```

**11.3.9 sys/ioctl.h**

```
#define TIOCGWINSZ      0x5413
#define FIONREAD        0x541B
#define TIOCNOTTY      21538
```

**11.3.10 sys/ipc.h**

```
struct ipc_perm
{
    key_t __key;
    uid_t uid;
    gid_t gid;
    uid_t cuid;
    uid_t cgid;
    unsigned short mode;
    unsigned short __pad1;
    unsigned short __seq;
    unsigned short __pad2;
    unsigned long int __unused1;
    unsigned long int __unused2;
};
```

**11.3.11 sys/mman.h**

```
#define MCL_CURRENT      1
#define MCL_FUTURE      2
```

**11.3.12 sys/msg.h**

```
typedef unsigned long int msgqnum_t;
typedef unsigned long int msglen_t;
```

```
struct msqid_ds
{
    struct ipc_perm msg_perm;
    time_t msg_stime;
    time_t msg_rtime;
    time_t msg_ctime;
    unsigned long int __msg_cbytes;
    msgqnum_t msg_qnum;
    msglen_t msg_qbytes;
    pid_t msg_lspid;
    pid_t msg_lrpid;
    unsigned long int __unused4;
    unsigned long int __unused5;
};
```

**11.3.13 sys/sem.h**

```
struct semid_ds
{
    struct ipc_perm sem_perm;
    time_t sem_otime;
    unsigned long int __unused1;
    time_t sem_ctime;
```

```

    unsigned long int __unused2;
    unsigned long int sem_nsems;
    unsigned long int __unused3;
    unsigned long int __unused4;
}
;

```

### 11.3.14 sys/shm.h

```

#define SHMLBA (__getpagesize())

typedef unsigned long int shmatt_t;

struct shmid_ds
{
    struct ipc_perm shm_perm;
    size_t shm_segsz;
    time_t shm_atime;
    time_t shm_dtime;
    time_t shm_ctime;
    pid_t shm_cpid;
    pid_t shm_lpid;
    shmatt_t shm_nattch;
    unsigned long int __unused4;
    unsigned long int __unused5;
}
;

```

### 11.3.15 sys/socket.h

```

typedef uint64_t __ss_aligntype;

#define SO_RCVLOWAT    18
#define SO_SNDLOWAT    19
#define SO_RCVTIMEO    20
#define SO_SNDTIMEO    21

```

### 11.3.16 sys/stat.h

```

#define _STAT_VER      1

struct stat
{
    dev_t st_dev;
    ino_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
    gid_t st_gid;
    int pad0;
    dev_t st_rdev;
    off_t st_size;
    blksize_t st_blksize;
    blkcnt_t st_blocks;
    struct timespec st_atim;
    struct timespec st_mtim;
    struct timespec st_ctim;
    unsigned long int __unused[3];
}
;

```



```

struct stat64
{
    dev_t st_dev;
    ino64_t st_ino;
    nlink_t st_nlink;
    mode_t st_mode;
    uid_t st_uid;
    gid_t st_gid;
    int pad0;
    dev_t st_rdev;
    off_t st_size;
    blksize_t st_blksize;
    blkcnt64_t st_blocks;
    struct timespec st_atim;
    struct timespec st_mtim;
    struct timespec st_ctim;
    unsigned long int __unused[3];
}
;

```

### 11.3.17 sys/statvfs.h

```

struct statvfs64
{
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt64_t f_blocks;
    fsblkcnt64_t f_bfree;
    fsblkcnt64_t f_bavail;
    fsfilcnt64_t f_files;
    fsfilcnt64_t f_ffree;
    fsfilcnt64_t f_favail;
    unsigned long int f_fsid;
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int __f_spare[6];
}
;
struct statvfs
{
    unsigned long int f_bsize;
    unsigned long int f_frsize;
    fsblkcnt_t f_blocks;
    fsblkcnt_t f_bfree;
    fsblkcnt_t f_bavail;
    fsfilcnt_t f_files;
    fsfilcnt_t f_ffree;
    fsfilcnt_t f_favail;
    unsigned long int f_fsid;
    unsigned long int f_flag;
    unsigned long int f_namemax;
    int __f_spare[6];
}
;

```

### 11.3.18 sys/types.h

```

typedef long int int64_t;

typedef int64_t ssize_t;

#define __FDSET_LONGS 16

```

**11.3.19 termios.h**

```

#define OLCUC      0000002
#define ONLCR     0000004
#define XCASE     0000004
#define NLDLY     0000400
#define CR1       0001000
#define IUCLC     0001000
#define CR2       0002000
#define CR3       0003000
#define CRDLY     0003000
#define TAB1      0004000
#define TAB2      0010000
#define TAB3      0014000
#define TABDLY    0014000
#define BS1       0020000
#define BSDLY     0020000
#define VT1       0040000
#define VTDLY     0040000
#define FF1       0100000
#define FFDLY     0100000

#define VSUSP     10
#define VEOL      11
#define VREPRINT  12
#define VDISCARD  13
#define VWERASE   14
#define VEOL2     16
#define VMIN      6
#define VSWTC     7
#define VSTART    8
#define VSTOP     9

#define IXON      0002000
#define IXOFF     0010000

#define CS6       0000020
#define CS7       0000040
#define CS8       0000060
#define CSIZE     0000060
#define CSTOPB    0000100
#define CREAD     0000200
#define PARENB    0000400
#define PARODD    0001000
#define HUPCL     0002000
#define CLOCAL    0004000
#define VTIME     5

#define ISIG      0000001
#define ICANON    0000002
#define ECHOE     0000020
#define ECHOK     0000040
#define ECHONL    0000100
#define NOFLSH    0000200
#define TOSTOP    0000400
#define ECHOCTL   0001000
#define ECHOPRT   0002000
#define ECHOKE    0004000
#define FLUSHO    0010000
#define PENDIN    0040000
#define IEXTEN    0100000

```

**11.3.20 ucontext.h**

```

struct _libc_fpxreg
{
    unsigned short significand[4];
    unsigned short exponent;
    unsigned short padding[3];
}
;

typedef long int greg_t;
#define NGREG    23

typedef greg_t gregset_t[23];

struct _libc_xmmreg
{
    uint32_t element[4];
}
;

struct _libc_fpstate
{
    uint16_t cwd;
    uint16_t swd;
    uint16_t ftw;
    uint16_t fop;
    uint64_t rip;
    uint64_t rdp;
    uint32_t mxcsr;
    uint32_t mxcr_mask;
    struct _libc_fpxreg _st[8];
    struct _libc_xmmreg _xmm[16];
    uint32_t padding[24];
}
;

typedef struct _libc_fpstate *fpregset_t;

typedef struct
{
    gregset_t gregs;
    fpregset_t fpregs;
    unsigned long int __reserved1[8];
}
mcontext_t;

typedef struct ucontext
{
    unsigned long int uc_flags;
    struct ucontext *uc_link;
    stack_t uc_stack;
    mcontext_t uc_mcontext;
    sigset_t uc_sigmask;
    struct _libc_fpstate __fpregs_mem;
}
ucontext_t;

```

**11.3.21 unistd.h**

```

typedef long int intptr_t;

```

**11.3.22 utmp.h**

```

struct lastlog
{
    int32_t ll_time;
    char ll_line[UT_LINESIZE];
    char ll_host[UT_HOSTSIZE];
}
;

struct utmp
{
    short ut_type;
    pid_t ut_pid;
    char ut_line[UT_LINESIZE];
    char ut_id[4];
    char ut_user[UT_NAMESIZE];
    char ut_host[UT_HOSTSIZE];
    struct exit_status ut_exit;
    int ut_session;
    struct
    {
        int32_t tv_sec;
        int32_t tv_usec;
    }
    ut_tv;
    int32_t ut_addr_v6[4];
    char __unused[20];
}
;

```

**11.3.23 utmpx.h**

```

struct utmpx
{
    short ut_type;
    pid_t ut_pid;
    char ut_line[UT_LINESIZE];
    char ut_id[4];
    char ut_user[UT_NAMESIZE];
    char ut_host[UT_HOSTSIZE];
    struct exit_status ut_exit;
    int32_t ut_session;
    struct
    {
        int32_t tv_sec;
        int32_t tv_usec;
    }
    ut_tv;
    int32_t ut_addr_v6[4];
    char __unused[20];
}
;

```

**11.4 Interfaces for libm**

Table 11-24 defines the library name and shared object name for the libm library

**Table 11-24 libm Definition**

Library:	libm
----------	------

SONAME:	libm.so.6
---------	-----------

The behavior of the interfaces in this library is specified by the following specifications:

ISO C (1999)  
 this specification  
 SUSv2  
 ISO POSIX (2003)

## 11.4.1 Math

### 11.4.1.1 Interfaces for Math

An LSB conforming implementation shall provide the architecture specific functions for Math specified in Table 11-25, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-25 libm - Math Function Interfaces**

__finite(GLIBC_2.2.5) [1]	ccosl(GLIBC_2.2.5) [2]	exp(GLIBC_2.2.5) [2]	j1f(GLIBC_2.2.5) [1]	pow10l(GLIBC_2.2.5) [1]
__finitef(GLIBC_2.2.5) [1]	ceil(GLIBC_2.2.5) [2]	exp2(GLIBC_2.2.5) [2]	j1l(GLIBC_2.2.5) [1]	powf(GLIBC_2.2.5) [2]
__finitel(GLIBC_2.2.5) [1]	ceilf(GLIBC_2.2.5) [2]	exp2f(GLIBC_2.2.5) [2]	jnl(GLIBC_2.2.5) [2]	powl(GLIBC_2.2.5) [2]
__fpclassify(GLIBC_2.2.5) [3]	ceill(GLIBC_2.2.5) [2]	exp2l(GLIBC_2.2.5) [2]	jnf(GLIBC_2.2.5) [1]	remainder(GLIBC_2.2.5) [2]
__fpclassifyf(GLIBC_2.2.5) [3]	cexp(GLIBC_2.2.5) [2]	expf(GLIBC_2.2.5) [2]	jnl(GLIBC_2.2.5) [1]	remainderf(GLIBC_2.2.5) [2]
__fpclassifyl(GLIBC_2.2.5) [1]	cexpf(GLIBC_2.2.5) [2]	expl(GLIBC_2.2.5) [2]	ldexp(GLIBC_2.2.5) [2]	remainderl(GLIBC_2.2.5) [2]
__signbitl(GLIBC_2.2.5) [1]	cexpl(GLIBC_2.2.5) [2]	expm1(GLIBC_2.2.5) [2]	ldexpf(GLIBC_2.2.5) [2]	remquo(GLIBC_2.2.5) [2]
acos(GLIBC_2.2.5) [2]	cimag(GLIBC_2.2.5) [2]	expm1f(GLIBC_2.2.5) [2]	ldexpl(GLIBC_2.2.5) [2]	remquof(GLIBC_2.2.5) [2]
acosf(GLIBC_2.2.5) [2]	cimagf(GLIBC_2.2.5) [2]	expm1l(GLIBC_2.2.5) [2]	lgamma(GLIBC_2.2.5) [2]	remquol(GLIBC_2.2.5) [2]
acosh(GLIBC_2.2.5) [2]	cimagl(GLIBC_2.2.5) [2]	fabs(GLIBC_2.2.5) [2]	lgamma_r(GLIBC_2.2.5) [1]	rint(GLIBC_2.2.5) [2]
acoshf(GLIBC_2.2.5) [2]	clog(GLIBC_2.2.5) [2]	fabsf(GLIBC_2.2.5) [2]	lgammaf(GLIBC_2.2.5) [2]	rintf(GLIBC_2.2.5) [2]
acoshl(GLIBC_2.2.5) [2]	clog10(GLIBC_2.2.5) [1]	fabsl(GLIBC_2.2.5) [2]	lgammaf_r(GLIBC_2.2.5) [1]	rintl(GLIBC_2.2.5) [2]

acosl(GLIBC_2.2.5) [2]	clog10f(GLIBC_C_2.2.5) [1]	fdim(GLIBC_2.2.5) [2]	lgammal(GLIBC_2.2.5) [2]	round(GLIBC_2.2.5) [2]
asin(GLIBC_2.2.5) [2]	clog10l(GLIBC_C_2.2.5) [1]	fdimf(GLIBC_2.2.5) [2]	lgammal_r(GLIBC_2.2.5) [1]	roundf(GLIBC_C_2.2.5) [2]
asinf(GLIBC_2.2.5) [2]	clogf(GLIBC_2.2.5) [2]	fdiml(GLIBC_2.2.5) [2]	llrint(GLIBC_2.2.5) [2]	roundl(GLIBC_C_2.2.5) [2]
asinh(GLIBC_2.2.5) [2]	clogl(GLIBC_2.2.5) [2]	feclearexcept(GLIBC_2.2.5) [2]	llrintf(GLIBC_2.2.5) [2]	scalb(GLIBC_2.2.5) [2]
asinhf(GLIBC_2.2.5) [2]	conj(GLIBC_2.2.5) [2]	fegetenv(GLIBC_2.2.5) [2]	llrintl(GLIBC_2.2.5) [2]	scalbf(GLIBC_2.2.5) [1]
asinhf(GLIBC_2.2.5) [2]	conjf(GLIBC_2.2.5) [2]	fegetexceptflag(GLIBC_2.2.5) [2]	llround(GLIBC_C_2.2.5) [2]	scalbl(GLIBC_2.2.5) [1]
asinl(GLIBC_2.2.5) [2]	conjl(GLIBC_2.2.5) [2]	fegetround(GLIBC_2.2.5) [2]	llroundf(GLIBC_C_2.2.5) [2]	scalbln(GLIBC_C_2.2.5) [2]
atan(GLIBC_2.2.5) [2]	copysign(GLIBC_2.2.5) [2]	feholdexcept(GLIBC_2.2.5) [2]	llroundl(GLIBC_C_2.2.5) [2]	scalblnf(GLIBC_C_2.2.5) [2]
atan2(GLIBC_2.2.5) [2]	copysignf(GLIBC_2.2.5) [2]	feraiseexcept(GLIBC_2.2.5) [2]	log(GLIBC_2.2.5) [2]	scalbln(GLIBC_C_2.2.5) [2]
atan2f(GLIBC_2.2.5) [2]	copysignl(GLIBC_2.2.5) [2]	fesetenv(GLIBC_C_2.2.5) [2]	log10(GLIBC_2.2.5) [2]	scalbn(GLIBC_2.2.5) [2]
atan2l(GLIBC_2.2.5) [2]	cos(GLIBC_2.2.5) [2]	fesetexceptflag(GLIBC_2.2.5) [2]	log10f(GLIBC_2.2.5) [2]	scalbnf(GLIBC_C_2.2.5) [2]
atanf(GLIBC_2.2.5) [2]	cosf(GLIBC_2.2.5) [2]	fesetround(GLIBC_2.2.5) [2]	log10l(GLIBC_2.2.5) [2]	scalbnl(GLIBC_C_2.2.5) [2]
atanh(GLIBC_2.2.5) [2]	cosh(GLIBC_2.2.5) [2]	fetestexcept(GLIBC_2.2.5) [2]	log1p(GLIBC_2.2.5) [2]	significand(GLIBC_2.2.5) [1]
atanhf(GLIBC_2.2.5) [2]	coshf(GLIBC_2.2.5) [2]	feupdateenv(GLIBC_2.2.5) [2]	log1pf(GLIBC_2.2.5) [2]	significandf(GLIBC_2.2.5) [1]
atanhl(GLIBC_2.2.5) [2]	coshl(GLIBC_2.2.5) [2]	finite(GLIBC_2.2.5) [4]	log1pl(GLIBC_2.2.5) [2]	significandl(GLIBC_2.2.5) [1]
atanl(GLIBC_2.2.5) [2]	cosl(GLIBC_2.2.5) [2]	finitef(GLIBC_2.2.5) [1]	log2(GLIBC_2.2.5) [2]	sin(GLIBC_2.2.5) [2]

cabs(GLIBC_2.2.5) [2]	cpow(GLIBC_2.2.5) [2]	finitel(GLIBC_2.2.5) [1]	log2f(GLIBC_2.2.5) [2]	sincos(GLIBC_2.2.5) [1]
cabsf(GLIBC_2.2.5) [2]	cpowf(GLIBC_2.2.5) [2]	floor(GLIBC_2.2.5) [2]	log2l(GLIBC_2.2.5) [2]	sincosf(GLIBC_2.2.5) [1]
cabsl(GLIBC_2.2.5) [2]	cpowl(GLIBC_2.2.5) [2]	floorf(GLIBC_2.2.5) [2]	logb(GLIBC_2.2.5) [2]	sincosl(GLIBC_2.2.5) [1]
cacos(GLIBC_2.2.5) [2]	cproj(GLIBC_2.2.5) [2]	floorl(GLIBC_2.2.5) [2]	logbf(GLIBC_2.2.5) [2]	sinf(GLIBC_2.2.5) [2]
cacosf(GLIBC_2.2.5) [2]	cprojf(GLIBC_2.2.5) [2]	fma(GLIBC_2.2.5) [2]	logbl(GLIBC_2.2.5) [2]	sinh(GLIBC_2.2.5) [2]
cacosh(GLIBC_2.2.5) [2]	cprojl(GLIBC_2.2.5) [2]	fmaf(GLIBC_2.2.5) [2]	logf(GLIBC_2.2.5) [2]	sinhf(GLIBC_2.2.5) [2]
cacoshf(GLIBC_2.2.5) [2]	creal(GLIBC_2.2.5) [2]	fmal(GLIBC_2.2.5) [2]	logl(GLIBC_2.2.5) [2]	sinhl(GLIBC_2.2.5) [2]
cacoshl(GLIBC_2.2.5) [2]	crealf(GLIBC_2.2.5) [2]	fmax(GLIBC_2.2.5) [2]	lrint(GLIBC_2.2.5) [2]	sinl(GLIBC_2.2.5) [2]
cacosl(GLIBC_2.2.5) [2]	creall(GLIBC_2.2.5) [2]	fmaxf(GLIBC_2.2.5) [2]	lrintf(GLIBC_2.2.5) [2]	sqrt(GLIBC_2.2.5) [2]
carg(GLIBC_2.2.5) [2]	csin(GLIBC_2.2.5) [2]	fmaxl(GLIBC_2.2.5) [2]	lrintl(GLIBC_2.2.5) [2]	sqrtf(GLIBC_2.2.5) [2]
cargf(GLIBC_2.2.5) [2]	csinf(GLIBC_2.2.5) [2]	fmin(GLIBC_2.2.5) [2]	lround(GLIBC_2.2.5) [2]	sqrtl(GLIBC_2.2.5) [2]
cargl(GLIBC_2.2.5) [2]	csinh(GLIBC_2.2.5) [2]	fminf(GLIBC_2.2.5) [2]	lroundf(GLIBC_2.2.5) [2]	tan(GLIBC_2.2.5) [2]
casin(GLIBC_2.2.5) [2]	csinhf(GLIBC_2.2.5) [2]	fminl(GLIBC_2.2.5) [2]	lroundl(GLIBC_2.2.5) [2]	tanf(GLIBC_2.2.5) [2]
casinf(GLIBC_2.2.5) [2]	csinhl(GLIBC_2.2.5) [2]	fmod(GLIBC_2.2.5) [2]	matherr(GLIBC_2.2.5) [1]	tanh(GLIBC_2.2.5) [2]
casinh(GLIBC_2.2.5) [2]	csinl(GLIBC_2.2.5) [2]	fmodf(GLIBC_2.2.5) [2]	modf(GLIBC_2.2.5) [2]	tanhf(GLIBC_2.2.5) [2]
casinhf(GLIBC_2.2.5) [2]	csqrt(GLIBC_2.2.5) [2]	fmodl(GLIBC_2.2.5) [2]	modff(GLIBC_2.2.5) [2]	tanhf(GLIBC_2.2.5) [2]
casinhl(GLIBC_2.2.5) [2]	csqrtf(GLIBC_2.2.5) [2]	frexp(GLIBC_2.2.5) [2]	modfl(GLIBC_2.2.5) [2]	tanl(GLIBC_2.2.5) [2]
casinl(GLIBC_2.2.5) [2]	csqrtl(GLIBC_2.2.5) [2]	frexpf(GLIBC_2.2.5) [2]	nan(GLIBC_2.2.5) [2]	tgamma(GLIBC_2.2.5) [2]
catan(GLIBC_2.2.5) [2]	ctan(GLIBC_2.2.5) [2]	frexpl(GLIBC_2.2.5) [2]	nanf(GLIBC_2.2.5) [2]	tgammaf(GLIBC_2.2.5) [2]
catanf(GLIBC_2.2.5) [2]	ctanf(GLIBC_2.2.5) [2]	gamma(GLIBC_2.2.5) [4]	nanl(GLIBC_2.2.5) [2]	tgammaf(GLIBC_2.2.5) [2]
catanh(GLIBC_2.2.5) [2]	ctanh(GLIBC_2.2.5) [2]	gammaf(GLIBC_2.2.5) [2]	nearbyint(GLIBC_2.2.5) [2]	trunc(GLIBC_2.2.5) [2]

_2.2.5) [2]	2.2.5) [2]	C_2.2.5) [1]	BC_2.2.5) [2]	2.2.5) [2]
catanhf(GLIBC_C_2.2.5) [2]	ctanhf(GLIBC_2.2.5) [2]	gammal(GLIBC_C_2.2.5) [1]	nearbyintf(GLIBC_2.2.5) [2]	truncf(GLIBC_2.2.5) [2]
catanhl(GLIBC_C_2.2.5) [2]	ctanhl(GLIBC_2.2.5) [2]	hypot(GLIBC_2.2.5) [2]	nearbyintl(GLIBC_2.2.5) [2]	truncl(GLIBC_2.2.5) [2]
catanl(GLIBC_2.2.5) [2]	ctanl(GLIBC_2.2.5) [2]	hypotf(GLIBC_2.2.5) [2]	nextafter(GLIBC_2.2.5) [2]	y0(GLIBC_2.2.5) [2]
cbrt(GLIBC_2.2.5) [2]	dremf(GLIBC_2.2.5) [1]	hypotl(GLIBC_2.2.5) [2]	nextafterf(GLIBC_2.2.5) [2]	y0f(GLIBC_2.2.5) [1]
cbrtl(GLIBC_2.2.5) [2]	dreml(GLIBC_2.2.5) [1]	ilogb(GLIBC_2.2.5) [2]	nextafterl(GLIBC_2.2.5) [2]	y0l(GLIBC_2.2.5) [1]
cbrtl(GLIBC_2.2.5) [2]	erf(GLIBC_2.2.5) [2]	ilogbf(GLIBC_2.2.5) [2]	nexttoward(GLIBC_2.2.5) [2]	y1(GLIBC_2.2.5) [2]
ccos(GLIBC_2.2.5) [2]	erfc(GLIBC_2.2.5) [2]	ilogbl(GLIBC_2.2.5) [2]	nexttowardf(GLIBC_2.2.5) [2]	y1f(GLIBC_2.2.5) [1]
ccosf(GLIBC_2.2.5) [2]	erfcf(GLIBC_2.2.5) [2]	j0(GLIBC_2.2.5) [2]	nexttowardl(GLIBC_2.2.5) [2]	y1l(GLIBC_2.2.5) [1]
ccosh(GLIBC_2.2.5) [2]	erfcf(GLIBC_2.2.5) [2]	j0f(GLIBC_2.2.5) [1]	pow(GLIBC_2.2.5) [2]	yn(GLIBC_2.2.5) [2]
ccoshf(GLIBC_2.2.5) [2]	erff(GLIBC_2.2.5) [2]	j0l(GLIBC_2.2.5) [1]	pow10(GLIBC_C_2.2.5) [1]	ynf(GLIBC_2.2.5) [1]
ccoshl(GLIBC_2.2.5) [2]	erfl(GLIBC_2.2.5) [2]	j1(GLIBC_2.2.5) [2]	pow10f(GLIBC_C_2.2.5) [1]	ynl(GLIBC_2.2.5) [1]

*Referenced Specification(s)*

[1]. ISO C (1999)

[2]. ISO POSIX (2003)

[3]. this specification

[4]. SUSv2

An LSB conforming implementation shall provide the architecture specific data interfaces for Math specified in Table 11-26, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-26 libm - Math Data Interfaces**

signgam(GLIBC_2.2.5) [1]				
--------------------------	--	--	--	--

*Referenced Specification(s)*

[1]. ISO POSIX (2003)



## 11.5 Data Definitions for libm

This section defines global identifiers and their values that are associated with interfaces contained in libm. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content.

These definitions are intended to supplement those provided in the referenced underlying specifications.

This specification uses ISO/IEC 9899 C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

### 11.5.1 fenv.h

```
#define FE_INVALID      0x01
#define FE_DIVBYZERO   0x04
#define FE_OVERFLOW    0x08
#define FE_UNDERFLOW   0x10
#define FE_INEXACT     0x20

#define FE_ALL_EXCEPT (FE_INEXACT | FE_DIVBYZERO | FE_UNDERFLOW |
FE_OVERFLOW | FE_INVALID)

#define FE_TONEAREST    0
#define FE_DOWNWARD    0x400
#define FE_UPWARD      0x800
#define FE_TOWARDZERO  0xc00

typedef unsigned short fexcept_t;

typedef struct
{
    unsigned short __control_word;
    unsigned short __unused1;
    unsigned short __status_word;
    unsigned short __unused2;
    unsigned short __tags;
    unsigned short __unused3;
    unsigned int __eip;
    unsigned short __cs_selector;
    unsigned int __opcode:11;
    unsigned int __unused4:5;
    unsigned int __data_offset;
    unsigned short __data_selector;
    unsigned short __unused5;
    unsigned int __mxcsr;
}
fenv_t;
#define FE_DFL_ENV      ((__const fenv_t *) -1)
```

### 11.5.2 math.h

```
#define fpclassify(x)    (sizeof (x) == sizeof (float) ?
__fpclassifyf (x) : sizeof (x) == sizeof (double) ? __fpclassify (x)
: __fpclassifyl (x))
#define signbit(x)      (sizeof (x) == sizeof (float)? __signbitf
(x) : sizeof (x) == sizeof (double)? __signbit (x) : __signbitl (x))
```

```
#define FP_ILOGE0 -2147483648
#define FP_ILOGBNAN -2147483648
```

## 11.6 Interfaces for libpthread

Table 11-27 defines the library name and shared object name for the libpthread library

**Table 11-27 libpthread Definition**

Library:	libpthread
SONAME:	libpthread.so.0

The behavior of the interfaces in this library is specified by the following specifications:

Large File Support  
this specification  
ISO POSIX (2003)

### 11.6.1 Realtime Threads

#### 11.6.1.1 Interfaces for Realtime Threads

An LSB conforming implementation shall provide the architecture specific functions for Realtime Threads specified in Table 11-28, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-28 libpthread - Realtime Threads Function Interfaces**

pthread_attr_getinheritsched(GLIBC_2.2.5) [1]	pthread_attr_getscope(GLIBC_2.2.5) [1]	pthread_attr_setschedpolicy(GLIBC_2.2.5) [1]	pthread_getschedparam(GLIBC_2.2.5) [1]	
pthread_attr_setschedpolicy(GLIBC_2.2.5) [1]	pthread_attr_setinheritsched(GLIBC_2.2.5) [1]	pthread_attr_setscope(GLIBC_2.2.5) [1]	pthread_setschedparam(GLIBC_2.2.5) [1]	

*Referenced Specification(s)*

[1]. ISO POSIX (2003)

### 11.6.2 Advanced Realtime Threads

#### 11.6.2.1 Interfaces for Advanced Realtime Threads

No external functions are defined for libpthread - Advanced Realtime Threads

### 11.6.3 Posix Threads

#### 11.6.3.1 Interfaces for Posix Threads

An LSB conforming implementation shall provide the architecture specific functions for Posix Threads specified in Table 11-29, with the full mandatory functionality as described in the referenced underlying specification.

Table 11-29 libpthread - Posix Threads Function Interfaces

<code>_pthread_cleanup_pop(GLIBC_2.2.5)</code> [1]	<code>pthread_cond_broadcast(GLIBC_2.3.2)</code> [2]	<code>pthread_join(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_destroy(GLIBC_2.2.5)</code> [2]	<code>pthread_setconcurrency(GLIBC_2.2.5)</code> [2]
<code>_pthread_cleanup_push(GLIBC_2.2.5)</code> [1]	<code>pthread_cond_destroy(GLIBC_2.3.2)</code> [2]	<code>pthread_key_create(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_init(GLIBC_2.2.5)</code> [2]	<code>pthread_setspecific(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_destroy(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_init(GLIBC_2.3.2)</code> [2]	<code>pthread_key_delete(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_rdlock(GLIBC_2.2.5)</code> [2]	<code>pthread_sigmask(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_getdetachstate(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_signal(GLIBC_2.3.2)</code> [2]	<code>pthread_kill(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_timedrdlock(GLIBC_2.2.5)</code> [2]	<code>pthread_testcancel(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_getguardsize(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_timedwait(GLIBC_2.3.2)</code> [2]	<code>pthread_mutex_destroy(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_timedwrlock(GLIBC_2.2.5)</code> [2]	<code>sem_close(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_getschedparam(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_wait(GLIBC_2.3.2)</code> [2]	<code>pthread_mutex_init(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_tryrdlock(GLIBC_2.2.5)</code> [2]	<code>sem_destroy(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_getstack(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_attr_destroy(GLIBC_2.2.5)</code> [2]	<code>pthread_mutex_lock(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_trywrlock(GLIBC_2.2.5)</code> [2]	<code>sem_getvalue(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_getstackaddr(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_attr_getpshared(GLIBC_2.2.5)</code> [2]	<code>pthread_mutex_trylock(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_unlock(GLIBC_2.2.5)</code> [2]	<code>sem_init(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_getstacksize(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_attr_init(GLIBC_2.2.5)</code> [2]	<code>pthread_mutex_unlock(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlock_wrlock(GLIBC_2.2.5)</code> [2]	<code>sem_open(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_init(GLIBC_2.2.5)</code> [2]	<code>pthread_cond_attr_setpshared(GLIBC_2.2.5)</code> [2]	<code>pthread_mutexattr_destroy(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlockattr_destroy(GLIBC_2.2.5)</code> [2]	<code>sem_post(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_setdetachstate(GLIBC_2.2.5)</code> [2]	<code>pthread_create(GLIBC_2.2.5)</code> [2]	<code>pthread_mutexattr_getpshared(GLIBC_2.2.5)</code> [2]	<code>pthread_rwlockattr_getpshared(GLIBC_2.2.5)</code> [2]	<code>sem_timedwait(GLIBC_2.2.5)</code> [2]
<code>pthread_attr_setguardsize(GLIBC_2.2.5)</code>	<code>pthread_detach(GLIBC_2.2.5)</code>	<code>pthread_mutexattr_gettype(GLIBC_2.2.5)</code>	<code>pthread_rwlockattr_init(GLIBC_2.2.5)</code>	<code>sem_trywait(GLIBC_2.2.5)</code>

[2]	.5) [2]	[2]	IBC_2.2.5) [2]	[2]
pthread_attr_setschedparam(GLIBC_2.2.5) [2]	pthread_equal(GLIBC_2.2.5) [2]	pthread_mutexattr_init(GLIBC_2.2.5) [2]	pthread_rwlockattr_setpshared(GLIBC_2.2.5) [2]	sem_unlink(GLIBC_2.2.5) [2]
pthread_attr_setstackaddr(GLIBC_2.2.5) [2]	pthread_exit(GLIBC_2.2.5) [2]	pthread_mutexattr_setpshared(GLIBC_2.2.5) [2]	pthread_self(GLIBC_2.2.5) [2]	sem_wait(GLIBC_2.2.5) [2]
pthread_attr_setstacksize(GLIBC_2.2.5) [2]	pthread_getconcurrency(GLIBC_2.2.5) [2]	pthread_mutexattr_settype(GLIBC_2.2.5) [2]	pthread_setcancelstate(GLIBC_2.2.5) [2]	
pthread_cancel(GLIBC_2.2.5) [2]	pthread_getspecific(GLIBC_2.2.5) [2]	pthread_once(GLIBC_2.2.5) [2]	pthread_setcanceltype(GLIBC_2.2.5) [2]	

Referenced Specification(s)

- [1]. this specification
- [2]. ISO POSIX (2003)

### 11.6.4 Thread aware versions of libc interfaces

#### 11.6.4.1 Interfaces for Thread aware versions of libc interfaces

An LSB conforming implementation shall provide the architecture specific functions for Thread aware versions of libc interfaces specified in Table 11-30, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-30 libpthread - Thread aware versions of libc interfaces Function Interfaces**

lseek64(GLIBC_2.2.5) [1]	pread(GLIBC_2.2.5) [2]	pwrite(GLIBC_2.2.5) [2]		
open64(GLIBC_2.2.5) [1]	pread64(GLIBC_2.2.5) [1]	pwrite64(GLIBC_2.2.5) [1]		

Referenced Specification(s)

- [1]. Large File Support
- [2]. ISO POSIX (2003)

### 11.7 Interfaces for libgcc\_s

Table 11-31 defines the library name and shared object name for the libgcc\_s library

**Table 11-31 libgcc\_s Definition**

Library:	libgcc_s
----------	----------

SONAME:	libgcc_s.so.1
---------	---------------

The behavior of the interfaces in this library is specified by the following specifications:

this specification

## 11.7.1 Unwind Library

### 11.7.1.1 Interfaces for Unwind Library

An LSB conforming implementation shall provide the architecture specific functions for Unwind Library specified in Table 11-32, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-32 libgcc\_s - Unwind Library Function Interfaces**

<code>_Unwind_Backtrace(GCC_3.0)</code> [1]	<code>_Unwind_ForcedUnwind(GCC_3.0)</code> [1]	<code>_Unwind_GetIP(GCC_3.0)</code> [1]	<code>_Unwind_RaiseException(GCC_3.0)</code> [1]	<code>_Unwind_SetIP(GCC_3.0)</code> [1]
<code>_Unwind_DeleteException(GCC_3.0)</code> [1]	<code>_Unwind_GetCFA(GCC_3.3)</code> [1]	<code>_Unwind_GetLanguageSpecificData(GCC_3.0)</code> [1]	<code>_Unwind_Resume(GCC_3.0)</code> [1]	
<code>_Unwind_FindEnclosingFunction(GCC_3.0)</code> [1]	<code>_Unwind_GetDataRelBase(GCC_3.0)</code> [1]	<code>_Unwind_GetRegionStart(GCC_3.0)</code> [1]	<code>_Unwind_Resume_or_Rethrow(GCC_3.3)</code> [1]	
<code>_Unwind_FindFDE(GCC_3.0)</code> [1]	<code>_Unwind_GetGR(GCC_3.0)</code> [1]	<code>_Unwind_GetTextRelBase(GCC_3.0)</code> [1]	<code>_Unwind_SetGR(GCC_3.0)</code> [1]	

*Referenced Specification(s)*

[1]. this specification

## 11.8 Interface Definitions for libgcc\_s

The following interfaces are included in libgcc\_s and are defined by this specification. Unless otherwise noted, these interfaces shall be included in the source standard.

Other interfaces listed above for libgcc\_s shall behave as described in the referenced base document.

## 11.9 Interfaces for libdl

Table 11-33 defines the library name and shared object name for the libdl library

**Table 11-33 libdl Definition**

Library:	libdl
SONAME:	libdl.so.2

The behavior of the interfaces in this library is specified by the following specifications:

this specification  
ISO POSIX (2003)

## 11.9.1 Dynamic Loader

### 11.9.1.1 Interfaces for Dynamic Loader

An LSB conforming implementation shall provide the architecture specific functions for Dynamic Loader specified in Table 11-34, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-34 libdl - Dynamic Loader Function Interfaces**

dladdr(GLIB C_2.2.5) [1]	dldclose(GLIB C_2.2.5) [2]	dlderror(GLIB C_2.2.5) [2]	dlopen(GLIB C_2.2.5) [1]	dlsym(GLIBC _2.2.5) [1]
--------------------------	----------------------------	----------------------------	--------------------------	-------------------------

*Referenced Specification(s)*

- [1]. this specification
- [2]. ISO POSIX (2003)

## 11.10 Interfaces for libcrypt

Table 11-35 defines the library name and shared object name for the libcrypt library

**Table 11-35 libcrypt Definition**

Library:	libcrypt
SONAME:	libcrypt.so.1

The behavior of the interfaces in this library is specified by the following specifications:

ISO POSIX (2003)

### 11.10.1 Encryption

#### 11.10.1.1 Interfaces for Encryption

An LSB conforming implementation shall provide the architecture specific functions for Encryption specified in Table 11-36, with the full mandatory functionality as described in the referenced underlying specification.

**Table 11-36 libcrypt - Encryption Function Interfaces**

crypt(GLIBC_2.2.5) [1]	encrypt(GLIB C_2.2.5) [1]	setkey(GLIBC _2.2.5) [1]		
------------------------	---------------------------	--------------------------	--	--

*Referenced Specification(s)*

- [1]. ISO POSIX (2003)

## 12 Libraries

An LSB-conforming implementation shall also support some utility libraries which are built on top of the interfaces provided by the base libraries. These libraries implement common functionality, and hide additional system dependent information such as file formats and device names.

### 12.1 Interfaces for libz

Table 12-1 defines the library name and shared object name for the libz library

**Table 12-1 libz Definition**

Library:	libz
SONAME:	libz.so.1

#### 12.1.1 Compression Library

##### 12.1.1.1 Interfaces for Compression Library

No external functions are defined for libz - Compression Library

### 12.2 Interfaces for libncurses

Table 12-2 defines the library name and shared object name for the libncurses library

**Table 12-2 libncurses Definition**

Library:	libncurses
SONAME:	libncurses.so.5

#### 12.2.1 Curses

##### 12.2.1.1 Interfaces for Curses

No external functions are defined for libncurses - Curses

### 12.3 Interfaces for libutil

Table 12-3 defines the library name and shared object name for the libutil library

**Table 12-3 libutil Definition**

Library:	libutil
SONAME:	libutil.so.1

The behavior of the interfaces in this library is specified by the following specifications:

this specification

## 12.3.1 Utility Functions

### 12.3.1.1 Interfaces for Utility Functions

An LSB conforming implementation shall provide the architecture specific functions for Utility Functions specified in Table 12-4, with the full mandatory functionality as described in the referenced underlying specification.

**Table 12-4 libutil - Utility Functions Function Interfaces**

forkpty(GLIB C_2.2.5) [1]	login_tty(GLIBC_2.2.5) [1]	logwtmp(GLIBC_2.2.5) [1]		
login(GLIBC_2.2.5) [1]	logout(GLIBC_2.2.5) [1]	openpty(GLIBC_2.2.5) [1]		

*Referenced Specification(s)*

[1]. this specification



## 13 Software Installation

### 13.1 Package Dependencies

The LSB runtime environment shall provide the following dependencies.

`lsb-core-amd64`

This dependency is used to indicate that the application is dependent on features contained in the LSB-Core specification.

These dependencies shall have a version of 3.0.

Other LSB modules may add additional dependencies; such dependencies shall have the format `lsb-module-amd64`.

### 13.2 Package Architecture Considerations

All packages must specify an architecture of `x86_64`. An LSB runtime environment must accept an architecture of `x86_64` even if the native architecture is different.

The `archnum` value in the Lead Section shall be `0x0001`.

## Annex A Alphabetical Listing of Interfaces

### A.1 libgcc\_s

The behavior of the interfaces in this library is specified by the following Standards.  
this specification

**Table A-1 libgcc\_s Function Interfaces**

_Unwind_Backtrace[1]	_Unwind_GetDataRelBase[1]	_Unwind_RaiseException[1]
_Unwind_DeleteException[1]	_Unwind_GetGR[1]	_Unwind_Resume[1]
_Unwind_FindEnclosingFunction[1]	_Unwind_GetIP[1]	_Unwind_Resume_or_Rethrow[1]
_Unwind_Find_FDE[1]	_Unwind_GetLanguageSpecificData[1]	_Unwind_SetGR[1]
_Unwind_ForcedUnwind[1]	_Unwind_GetRegionStart[1]	_Unwind_SetIP[1]
_Unwind_GetCFA[1]	_Unwind_GetTextRelBase[1]	

### A.2 libm

The behavior of the interfaces in this library is specified by the following Standards.  
ISO C (1999)  
ISO POSIX (2003)

**Table A-2 libm Function Interfaces**

__fpclassify[1]	__signbit[1]	exp2l[1]
-----------------	--------------	----------

# Annex B GNU Free Documentation License

Version 1.1, March 2000

Copyright (C) 2000 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

## B.1 PREAMBLE

The purpose of this License is to make a manual, textbook, or other written document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

## B.2 APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you".

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (For example, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, whose

contents can be viewed and edited directly and straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup has been designed to thwart or discourage subsequent modification by readers is not Transparent. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML designed for human modification. Opaque formats include PostScript, PDF, proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

### **B.3 VERBATIM COPYING**

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

### **B.4 COPYING IN QUANTITY**

If you publish printed copies of the Document numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a publicly-accessible computer-network location containing a complete Transparent copy of the Document, free of added material, which the general network-using public has access to download

anonymously at no charge using public-standard network protocols. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

## B.5 MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has less than five).
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section entitled "History", and its title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work

that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

- K. In any section entitled "Acknowledgements" or "Dedications", preserve the section's title, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section as "Endorsements" or to conflict in title with any Invariant Section.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

## **B.6 COMBINING DOCUMENTS**

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections entitled "History" in the various original documents, forming one section entitled "History"; likewise combine any

sections entitled "Acknowledgements", and any sections entitled "Dedications". You must delete all sections entitled "Endorsements."

## **B.7 COLLECTIONS OF DOCUMENTS**

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

## **B.8 AGGREGATION WITH INDEPENDENT WORKS**

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, does not as a whole count as a Modified Version of the Document, provided no compilation copyright is claimed for the compilation. Such a compilation is called an "aggregate", and this License does not apply to the other self-contained works thus compiled with the Document, on account of their being thus compiled, if they are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one quarter of the entire aggregate, the Document's Cover Texts may be placed on covers that surround only the Document within the aggregate. Otherwise they must appear on covers around the whole aggregate.

## **B.9 TRANSLATION**

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License provided that you also include the original English version of this License. In case of a disagreement between the translation and the original English version of this License, the original English version will prevail.

## **B.10 TERMINATION**

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

## **B.11 FUTURE REVISIONS OF THIS LICENSE**

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in

spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

## **B.12 How to use this License for your documents**

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright (c) YEAR YOUR NAME. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.1 or any later version published by the Free Software Foundation; with the Invariant Sections being LIST THEIR TITLES, with the Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST. A copy of the license is included in the section entitled "GNU Free Documentation License".

If you have no Invariant Sections, write "with no Invariant Sections" instead of saying which ones are invariant. If you have no Front-Cover Texts, write "no Front-Cover Texts" instead of "Front-Cover Texts being LIST"; likewise for Back-Cover Texts.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.